

V2

2915 Ogletown RD # 2270 Newark, DE 19713 T.+1-866-650-6555 F.+1-888-966-6555 quotes@motioncomposites.com orders@motioncomposites.com www.motioncomposites.com

25" (559) wheel

26" (590) wheel

EVO Program - I	Rigid
-----------------	-------

	-	
ORDER	FORM	- USA

1- Purchasir	ng inform	ation				3- Shipping information				
P.O. numbe	r:*		Date:			Ship to:*				
Company Na	ame:*				_	Name:				_
Purchasing of	contact:*				_	Address:				_
Phone:*					_	City:		Province:		_
Email:*					_	Postal Code:				_
	foronco:*	Phone	Email 🗆		_	Phone:				-
Contact pre		Phone 🗆	EMINI U		_	Priorie:				-
Marked for:					_					7
2- Dealer/R	epresenta	tive information								
Dealer/Repr	resentativ	e:*			_					
Phone:*						Original Serial or Purchase Or	der Number	*:		
Email:*										
Contact pre	ference:*	Phone □	Email 🗆		_					
					_					
* Required									Taxes no	t included
MODEL										
WC11		Aluminum frame				frame, open loop or tube and clamp ge), receivers and clamps for	s,			\$1,560
		Carbon fiber frame				lock, side guard, armrest, anti-tippe	rs),			
WC21		(High Gloss Carbon Fiber)		STD slip-on (only if width ch	hange), rigidizer,	camber bushing, WC-19.				\$2,440
SEAT WIDTH	1									
SW		Original configuration	12" 🗆	13″ □	14" □	15" □				NC
		16" □	17" 🗆	18" □	19" □	20" 🗆				
SEAT DEPTH			"	-2"		.="				
SD		Original configuration 16"	12" □ 17" □	13" □	14" 🗆	15" □				NC
FRAME LEN	GTH	16" □	17 🗆	18" □	19" 🗆	20" 🗆				
T NAME EET		Original configuration								STD
SP01		Standard frame length conf	iguration ¹							NC
SP02		Frame length 1" longer than	standard configu	ration						NC
SP03		Frame length 2" longer than	standard configu	ration						NC
SP04		Frame length 1" shorter tha	n standard config	uration						NC
SP05		Frame length 2" shorter tha	n standard config	uration						NC
TIE-DOWN		ı	2							
AC05-S		WC-19 Transit Tie Down w/			elt 20"-41"					\$515
AC05-L		WC-19 Transit Tie Down w/		Long be	lt 20"-46"					\$515
AC35	of 4 37" from	WC-19 Transit Tie Down wit m end of seat upholstery to bend;		lled in the original configuration	n will he installed v	with no additional fees				\$354
1 Distance o	,, 4.57 ,101	mena of seat apholstery to bena,		FRONT Seat-to-floo		vici no addicional jees.		1		
		Caster sizes		Height available +- 1/4"						
		Original configuration		Use original configuration	n					
		3" Caster		14" to 21"		Specify desired hei	ht:			
		3 custer		14 (021		Specify desired field	····	W RIF		
		4" Caster		14.5" to 21")))) []	
		5" Caster		15.5" to 21"		(inc	hes)			
		J Castel							@-J +	
		6" Caster		16.5" to 21" (N/A with 90° front frame	2)					
								4		
				REAR Seat-to-floor				\Box		
	_	Wheel sizes Original configuration		Height available +- 1/4" Use original configuration				ή		
		20" (451) wheel		14" to 17.5"	II .	Specify desired hei	ht:			
		22" (501) wheel		14" to 17.5"		Specify desired field	·····	TO TO		
		24" (540) wheel		15" to 19.5"		/:	hac)))) M	
		24 (340) WIIEEI		13 (0 13.3		(inc	hes)		/// []	

15.5" to 20"

16" to 20"

FRONT FRAM	ME ANGLI			
		Original configuration		STD
FA70		70° Front frame angle		NC
FA75		75° Front frame angle		NC
FA80		80° Front frame angle		NC
FA85		85° Front frame angle		NC
FA90		90° Front frame angle		NC

Seat upholstery to footplate length				
12" to 19" without high mount	Specify desired length:			
7" to 13" with high mount	(inches)			
	Required			

		Footrest v	vidth / Taper selection
Seat Width	Straight	1" Taper	2" Taper
Outside Measurement	2 ½" Narrower than	4 ½" Narrower than	6 ½" Narrower than
	Seat Width	Seat Width	Seat Width
12"	9.5''	7.5"	
13"	10.5"	8.5"	
14"	11.5"	9.5"	
15"	12.5"	10.5"	
16"	13.5"	11.5"	9.5"
17"	14.5"	12.5"	10.5"
18"	15.5"	13.5"	11.5"
19"	16.5"	14.5"	12.5"
20"	17.5"	15.5"	13.5"


Note: higher than 20" Front STFH will reduce the footrest width up to 1" with a 2" taper

REAR WHEE	L CAMBE	ER .	
CMOO		Original configuration	STD
CM00		0° camber	NC NC
CM02		2° camber	NC NC
CM04		4° camber	NC NC
CM06		6° camber	NC NC
CM08		8° camber	NC NC
CENTER OF	GRAVITY		
		of rear wheel axle plate: front of back post to center of axle receiver.	

If not indicated, default setting is at 2.5"

0 - 6" range

Motion Composites will select the closest possible center of gravity (COG) if an issue arises with the COG



By checking this box and submitting this EVO program order form, you confirm your agreement and commitment to take necessary actions to apply the terms and conditions, and communicate the EVO program terms and conditions to the user.

(inches)

NOTE: IF ANY OF THE ABOVE IS not SPECIFIED, ORIGINAL CONFIGURATION WILL BE USED.

Now is the time to change!

Any custom parts or colored camber tube from the previous configuration, will need to be reordered.

This is a great time to order new options and accessories, write them in below

Please refer to the parts list for pricing: https://www.motioncomposites.com/en-ca/support-and-education/for-professionals/tools-and-forms/parts-price-lists

Notes:			