



Helio A6

ORDER FORM - MANITOBA POSSIBLE

1- Purchasing information

P.O. number: * _____ Date: _____

Company Name: * _____

Purchasing contact: * _____

Phone: * _____

Email: * _____

Contact preference: * Phone ☐ Email ☐

Marked for: _____

3- Shipping information

Ship to: * **Manitoba Wheelchair Program**

Name: _____

Address: **1857 Notre Dame Ave.**

City: **Wpg** Province: **MB**

Postal Code: **R3E 3E7**

Phone: **204-975-3250**

NC = NO CHARGE (option available through Manitoba Possible)

J = JUSTIFICATION REQUIRED (provide clinical rationale)

OTP = OPTION TO PURCHASE (client responsible for cost)

N/A = NOT AVAILABLE (option not available through Manitoba Possible)

* Required MA080  English Manual (STD) Taxes not included

MODEL										
WC19	☐	Ultralight folding Helio A6 Wheelchair - 6000 series aluminum (265lb weight capacity)							NC	
WC09	☐	HD Heavy duty kit (350 lb weight capacity)							NC	
Frame										
SEAT WIDTH ³										
SW	☐	14" ☐	15" ☐	16" ☐	17" ☐	18" ¹ ☐			NC	
	☐	19" ¹ ☐	20" ¹ ☐	21" ² ☐	22" ² ☐			NC		
SEAT DEPTH										
SD	☐	14" ☐	15" ☐	16" ☐	17" ☐	18" ☐			NC	
	☐	19" ☐	20" ☐					NC		
TRANSIT TIE DOWN										
AC04	☐	Transit Tie Down (Unoccupied)							NC	
AC05-S	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Short belt 20"-41"							J	
AC05-L	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Long belt 20"-46"							J	
AC35	☐	WC-19 Transit Tie Down without belt ⁴							J	

1- Available with HD Kit (350 lb)

2- Only with HD Kit (350 lb)

3- Width calculator

4- May interfere with swing away armrest and Clamp on height adjustable push handle; Not available with HD option

A6 FRONT Seat-to-floor Height - Please select your choice

Forks / Position		3" caster (OTP)			4" caster (OTP)			5" caster (J)			6" caster (NC)			7" caster (OTP)			8" caster (NC)		
		Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length		
4"	P1	12"	13"	14"	12 1/2"	13 1/2"	14 1/2"												
	P2	12 1/2"	13 1/2"	14 1/2"	13"	14"	15"		14 1/2"	15 1/2"									
5"	P1																		
	P2				13"	14"	15"	13 1/2"	14 1/2"	15 1/2"									
	P3	13"	14"	15"	13 1/2"	14 1/2"	15 1/2"	14"	15"	16"		15 1/2"	16 1/2"						
	P4	13 1/2"	14 1/2"	15 1/2"	14"	15"	16"	14 1/2"	15 1/2"	16 1/2"	15"	16"	17"		16 1/2"	17 1/2"			
7"	P1										15 1/2"	16 1/2"	17 1/2"	16"	17"	18"			
	P2							15 1/2"	16 1/2"	17 1/2"	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"			
	P3							16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"
	P4	15 1/2"	16 1/2"	17 1/2"	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"
	P5	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"	18 1/2"	19 1/2"	20 1/2"

Height available +/- 1/4" (see stem bolt and fork combination at the end of the order form); Orange boxes are not available with a seat slope of more than 1.5in.

CASTERS				Availability		
CA01-03 to CA01-08	☐	Composite wheel w/ PU tire (1")		3", 4", 5", 6", 7", 8"		NC
CA10 to CA11	☐	Pneumatic casters (1 ¼")		6", 8"		OTP
CA14 to CA16	☐	Newton UltraCaster Composite (1 ½ ")		4", 5", 6"		J
CA17 to CA19	☐	Newton UltraCaster Aluminum (1 ½ ")		4", 5", 6"		OTP
CASTER OPTIONS						
CA12	☐	Caster Pin Locks (Available with +1" or +2" Stem bolt ONLY) ¹				OTP
CA13	☐	Carbon fiber Frog Legs suspension forks (Not available with caster pin locks)				OTP

1- Not available with WC-19

Helio A6 - REAR Seat-to-floor Height - Please select your choice

20" (451) (NC)	22" (501) (NC)	24" (540) (NC)	25" (559) (OTP)	26" (590) (OTP)
12"	13"	13 3/4"	14 1/4"	14 3/4"
12 1/2"	13 1/2"	14 1/4"	14 3/4"	15 1/4"
13"	14"	14 3/4"	15 1/4"	15 3/4"
13 1/2"	14 1/2"	15 1/4"	15 3/4"	16 1/4"
14"	15"	15 3/4"	16 1/4"	16 3/4"
14 1/2"	15 1/2"	16 1/4"	16 3/4"	17 1/4"
15"	16"	16 3/4"	17 1/4"	17 3/4"
15 1/2"	16 1/2"	17 1/4"	17 3/4"	18 1/4"
16"	17"	17 3/4"	18 1/4"	18 3/4"
16 1/2"	17 1/2"	18 1/4"	18 3/4"	19 1/4"
17"	18"	18 3/4"	19 1/4"	19 3/4"
17 1/2"	18 1/2"	19 1/4"	19 3/4"	20 1/4"

Configuration used: 1" seat slope with a center of gravity at 2"

Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- ½" of selected seat to floor height"

Footrest						
SWING-IN/SWING-OUT FOOTREST						
FR03-01	☐	60° Swing-in/swing-out footrest - 13.5" - 17"		Set at: *		NC
FR03-02	☐	60° Swing-in/swing-out footrest - 14.5" - 19.5"		Set at: *		NC
FR03-03	☐	60° Swing-in/swing-out footrest - 15.5" - 20.5"		Set at: *		NC
FR04-01	☐	70° Swing-in/swing-out footrest - 13.5" - 17"		Set at: *		NC
FR04-02	☐	70° Swing-in/swing-out footrest - 14.5" - 19.5"		Set at: *		NC
FR04-03	☐	70° Swing-in/swing-out footrest - 15.5" - 20.5"		Set at: *		NC
FR15-01	☐	80° Swing-in/swing-out footrest - 13.5" - 16" ⁵		Set at: *		NC
FR15-02	☐	80° Swing-in/swing-out footrest - 14.5" - 19.5" ⁵		Set at: *		NC
FR15-03	☐	80° Swing-in/swing-out footrest - 15.5" - 20.5" ⁵		Set at: *		NC
FR06	☐	90° swing-in/swing-out with front mount - Standard (no extension) ¹	7.5" - 11"	Set at: *		NC
FR07	☐	90° swing-in/swing-out with front mount - Short extension 2" ^{1, 2}	9.5"- 13"	Set at: *		NC
FR08	☐	90° swing-in/swing-out with front mount - Medium extension 4" ^{1, 2}	9.5" - 14.5"	Set at: *		NC
FOOTREST OPTIONS						
FR09	☐	High mount (footplate attached to the hanger with clamps) ³	5" - 13.5"	Set at: *		J
FR10	☐	Elevating legrest with calf pad, Length adjustable ⁴ Left ☐ Right ☐	14" - 22"	Set at:		J
FR99	☐	Omit Footrest				N/A

1- Available only with two piece adjustable footplates; 2- May interfere with front casters; 3- Not available with front mount and the elevating legrest; * +/- 1/2"

4- The elevating legrest replace the footrest side selected; Not available with one piece footplate; 5- Not available with 8" caster

FOOTPLATES						
FP01	☐	Standard - Composite ¹				NC
FP02	☐	Newton adjustable angle - Composite				J
FP03	☐	Newton adjustable angle - Aluminum				OTP
FP06	☐	One piece adjustable angle flip-up - Aluminum				OTP
FOOTPLATE ACCESSORIES						
FP08	☒	Length adjustable heel loop ²				NC
FP09	☐	Calf strap				OTP
FP30	☐	Bodypoint Aeromesh Padded calf strap				OTP

1- Not available with front mount; 2- not available with one piece footplate

SWING AWAY RESIDUAL LIMB SUPPORT							
FR27	☐	Residual limb support - flat 6"x8"	Left ☐ Right ☐				OTP
FR28	☐	Residual limb support - flat 8"x10"	Left ☐ Right ☐				OTP
FR29	☐	Residual limb support - flat 10"x10"	Left ☐ Right ☐				OTP
FR30	☐	Residual limb support - flat 10"x14"	Left ☐ Right ☐				OTP
FR32	☐	Residual limb support - contour 6"x8"	Left ☐ Right ☐				OTP
FR33	☐	Residual limb support - contour 8"x10"	Left ☐ Right ☐				OTP

Backrest							
FIXED ANGLE BACK CANES WITH INTEGRATED PUSH HANDLE <i>(push handle included - no further selection needed)</i>							
BC58-915	☐	Straight aluminum back cane	9" - 15" <i>increment of 1/2"</i>	Set at ² :			NC
BC58-1521	☐	Straight aluminum back cane	15" - 21" <i>increment of 1/2"</i>	Set at ² :			NC
BC60	☐	Straight aluminum back cane	21" - 24" <i>increment of 1"</i>	Set at ² :			J
BC01-16	☐	8° bend aluminum back cane	16"				NC
BC01-18	☐	8° bend aluminum back cane	18"				NC
BC01-20	☐	8° bend aluminum back cane	20"				NC
BC59	☐	8° bend aluminum back cane	21" - 24" <i>increment of 1"</i>	Set at ² :			J
FIXED ANGLE, HEIGHT ADJUSTABLE BACK CANES WITH PUSH HANDLE OPTIONS <i>(MUST select ONE push handle options)</i>							
BC11-912	☐	Straight aluminum back cane	9" - 12" <i>increment of 1/2"</i>	Set at ² :			J
BC11-1215	☐	Straight aluminum back cane	12" - 15" <i>increment of 1/2"</i>	Set at ² :			J
BC11-1518	☐	Straight aluminum back cane	15" - 18" <i>increment of 1/2"</i>	Set at ² :			J
BC11-1821	☐	Straight aluminum back cane	18" - 21" <i>increment of 1/2"</i>	Set at ² :			J
BC12-1315	☐	8° bend aluminum back cane	13.5" - 15" <i>increment of 1/2"</i>	Set at ² :			OTP
BC12-1518	☐	8° bend aluminum back cane	15" - 18" <i>increment of 1/2"</i>	Set at ² :			OTP
BC12-1821	☐	8° bend aluminum back cane	18" - 21" <i>increment of 1/2"</i>	Set at ² :			OTP
ANGLE AND HEIGHT ADJUSTABLE BACK CANE WITH PUSH HANDLE OPTIONS <i>(MUST select ONE push handle options)</i>							
BC13-1518	☐	Straight aluminum back cane	15" - 18" <i>increment of 1/2"</i>	Set at ² :			J
BC13-1821	☐	Straight aluminum back cane	18" - 21" <i>increment of 1/2"</i>	Set at ² :			J
BC14-1518	☐	8° bend aluminum back cane	15" - 18" <i>increment of 1/2"</i>	Set at ² :			OTP
BC14-1821	☐	8° bend aluminum back cane	18" - 21" <i>increment of 1/2"</i>	Set at ² :			OTP
		Select back cane angle:	85° ¹ ☐ 90° ☐ 95° STD ☐ 100° ☐ 105° ☐ 110° ☐				

PUSH HANDLES OPTIONS <i>(ONE option at a time)</i>						
PH01	☐	Push handles				NC
PH05	☐	Fold down push handles ^{3, 5}				OTP
PH06-920	☐	Clamp on height adjustable push handles 9"-20" ^{3,4, 5}				OTP
PH06-923	☐	Clamp on height adjustable push handles 9"-23" ^{3,4, 5}				OTP
PH02	☐	Omit push handles				NC
STROLLER HANDLE AND STABILIZER BAR <i>(only available with push handle)</i>						
PH04	☐	Stroller handle <i>(not available with the HD option)</i>				OTP
PH03	☐	Newton folding stabilizer bar <i>(not available with stroller handle)</i>				OTP

1- Not compatible with 8 degree bent back cane; 2- If not indicated, default height setting is at the lowest position; measured from seat sling to top of back upholstery; 3- 265lb weight limit

4- Not compatible with swing away armrests, 8° bend back canes, 21-24" back canes and amputee axle plates; 5- Not compatible with stroller handler, stabilizer bar, headrest and attendant lock;

BACK UPHOLSTERY						
BH05	☐	Slip-on Nylon back upholstery				NC
BH06	☐	Adjustable tension Nylon back upholstery				OTP
BH99	☐	Omit Back upholstery				NC
	☐	NXT back Support		See pricelist		OTP
SEAT CUSHION						
SC01	☐	2" Cushion				OTP
SC02	☐	3" Cushion				OTP
SC99	☐	Omit seat cushion				NC
	☐	NXT cushion			See price list	OTP

Rear wheels													
ONE ARM DRIVE ¹		Only available with Newton One rear wheel, permanent axles and 0° camber											
HR22	☐	One arm drive - aluminum inner handrim ^{2, 3}	24"	Left ☐	Right ☐		J						
HR60	☐	One arm drive - plastic coated inner handrim ^{2, 3}	24"	Left ☐	Right ☐		OTP						
HR98	☐	Omit handrim on opposite side of the One Arm Drive (OAD)					OTP						
REAR WHEELS						Available							
RW01	☐	Mag ⁴				20", 22" 24"	OTP						
RW02	☐	Newton One - spoke wheel ⁵				20", 22" 24"	NC						
RW03	☐	Newton Gravity - ultralight wheel				20", 22", 24", 25", 26"	OTP						
RW04	☐	Spinergy Spox	Blk STD ☐	Wht ⁶ ☐	Blue ⁶ ☐	Red ⁶ ☐	Yel ⁶ ☐	22", 24", 25", 26"	OTP				
RW05	☐	Spinergy LX	Blk STD ☐	Pur ⁶ ☐	Wht ⁶ ☐	Blue ⁶ ☐	Red ⁶ ☐	Yel ⁶ ☐	Pink ⁶ ☐	Grn ⁶ ☐	Org ⁶ ☐	22", 24", 25", 26"	OTP
RW07	☐	Spinergy CLX ⁷	Blk STD ☐	Pur ⁶ ☐	Wht ⁶ ☐	Blue ⁶ ☐	Red ⁶ ☐	Yel ⁶ ☐	Pink ⁶ ☐	Grn ⁶ ☐	Org ⁶ ☐	24", 25"	OTP
TIRES						Available							
Solid													
TI01	☐	Soft Urethane 1 3/8"				20", 22" 24"	NC						
TI02	☐	Soft Urethane knobby 1 3/8" ⁸				22", 24", 25", 26"	J						
TI04	☐	Soft Urethane 1" - <i>Shox</i>				22", 24", 25", 26"	OTP						
Pneumatic													
TI05	☐	Pneumatic 1 3/8"				20", 22", 24", 25", 26"	NC						
TI08	☐	Pneumatic with Airless insert 1 3/8" ⁹				22", 24", 26"	OTP						
TI06	☐	Pneumatic HP, Low Tread, Puncture resistant, black 1" - <i>SpeedLite</i>				20", 22", 24", 25", 26"	OTP						
TI07	☐	Pneumatic HP, Medium Tread, Puncture resistant, black 1" - <i>TrailBlazer</i>				24", 25", 26"	OTP						

1- Offered with handrims on each side of the wheelchair; select the outer handrim in the handrims section; 2- Only standard handrim position available; 3- Not available with HD option
4- Not compatible with HP tires ; Only available with aluminum or plastic coated handrim, standard position; 5- Not compatible with Shox tires; 6- color spokes require an additionnal 10 days lead-time;
7- Only available with 1" tires; 8- 22" is only available with Mags and Newton One rear wheels; 9- Not available with Spinergy CLX, Spinergy LX 25", 26" and Spox 25", 26" rear wheels

Handrims							
HANDRIM				Available			
HR01	☐	Aluminum anodized		20", 22", 24", 25", 26"			NC
HR61	☐	Aluminum black hard anodized ²		20", 22", 24", 25"			OTP
HR02	☐	Plastic coated ¹		20", 22", 24", 25", 26"			OTP
HR03	☐	High friction coated ^{1,2,3}		22", 24", 25", 26"			OTP
HR07-HR18 and HR65-HR71	☐	Newton Air Grip ² <i>See page 6 for the color selection and price</i>		20", 22", 24", 25", 26"			J
HR28	☐	Surge ^{1,2,3,4} (1 1/2" Oval handrim w/ Gripton high friction strip)		22", 24", 25", 26"			OTP
HR05	☐	Surge LT ^{1,2,3,4} (1 1/8" Oval handrim w/ Gripton high friction strip)		22", 24", 25", 26"			OTP
HR04	☐	Natural Fit ^{1,2,3,4}		22", 24", 25", 26"			OTP
HR62	☐	Simi H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)		22", 24", 25", 26"			OTP
HR63	☐	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)		22", 24", 25", 26"			OTP
HR64	☐	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)		22", 24", 25", 26"			OTP
HR99	☐	Omit handrim					NC

1- Only standard and narrow handrim position. By default, the tab won't be cut with the narrow position; 2- Not available with Mag wheels; 3 - Not available with one arm drive;
4- 25" and 26" are not available in narrow position; 24" is not available with the Spinergy Spox, LX and CLX in narrow position; CLX rear wheel are not available with thumb piece

Handrims option							
ASSEMBLY POSITION							
HR29	☐	Standard Handrim position	Full tab				NC
HR030	☐	Narrow Handrim position no cut	Full tab				NC
HR30	☐	Narrow Handrim position with cut ⁵	Short tab 2 positions				J
HR31	☐	Super Narrow Handrim ⁵	Short tab 2 positions STD ☐ Short tab 1 position ☐				J
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS							
HR23	☐	Standard grip					OTP
HR27	☐	Super grip					OTP
HR099	☐	Omit thumb piece					OTP

5- Only available with Aluminum and Air Grip handrims;

AXLE							
AX01	☐	Quick release axle ¹					NC
AX02	☐	Permanent axle					J
AX03	☐	Quad release axle ¹					OTP
AXLE PLATE							
AX04	☐	Amputee adjustable axle plate ²					OTP

1- Not required with one arm drive; 2 - May interfere with swing away armrest and limit seat to floor height

REAR WHEEL CAMBER				
CM00	☐	0° camber		NC
CM03	☐	3° camber		NC

Choose position of rear wheel axle plate:

Measure distance from front of back post to center of axle receiver.

Default setting is at 1 1/4"

Most stable						Most responsive
AMPUTEE ¹	3/4"	1" 1/4	1" 3/4	2" 1/4	2" 3/4	
☐	☐	☐	☐	☐	☐	

Motion Composites will select the closest possible center of gravity (COG) if an issue arises with the COG

1- Only available with amputee axle plate

WHEEL LOCK				
WL08	☐	Newton Wheel lock - push to lock	PRODUCT IMPROVED	NC
WL14	☐	6" removable extension handle for push to lock		J
WL16	☐	Aluminum push to lock with extensions		NC
WL02	☐	Pull to lock		J
WL04	☐	Newton grade aid push to lock (works best with pneumatic or high pressure tire)		OTP
WL13	☐	6" removable extension handle for pull to lock and grade aid		J
WL05	☐	Scissors Lock		OTP
WL06	☐	Attendant Lock (additional set of wheel lock mounted to the back)		OTP
WL15	☐	Unilateral wheel lock - pull to lock ¹ Left ☐ Right ☐		OTP
WL99	☐	Omit wheel locks		NC

1- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:
https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

Armrests				
HEIGHT ADJUSTABLE FLIP BACK ARMREST (Convertible to "T" armrest) ^{1,4}				
AR01-812	☐	10" Desk length armpad 8" - 12"	Locked ☐ Unlocked STD ☐	NC
AR01-1014	☐	10" Desk length armpad 10" - 14"	Locked ☐ Unlocked STD ☐	NC
AR02-812	☐	14" Full length armpad 8" - 12"	Locked ☐ Unlocked STD ☐	NC
AR02-1014	☐	14" Full length armpad 10" - 14"	Locked ☐ Unlocked STD ☐	NC
HEIGHT ADJUSTABLE "T" ARMREST ¹				
AR13-610	☐	10" Desk length armpad ⁵ 6" - 10"		NC
AR13-812	☐	10" Desk length armpad 8" - 12"		NC
AR13-1014	☐	10" Desk length armpad 10" - 14"		NC
AR14-610	☐	14" Full length armpad ⁵ 6" - 10"		NC
AR14-812	☐	14" Full length armpad 8" - 12"		NC
AR14-1014	☐	14" Full length armpad 10" - 14"		NC
SWING AWAY ARMREST ²				
AR05	☐	Tubular armrest - Short pad 8" - 11"		J
AR23	☐	Tubular armrest - long pad 8" - 11"		J
AR06	☐	10" Desk length flat armpad 8" - 11"		J
AR17	☐	14" Full length flat armpad 8" - 11"		J
ARMREST OPTIONS				
AR12	☐	14" Full Length armpad - Gel Ovation (pair) ³		OTP
AR99	☐	Omit armrest		J

1- May have 1/2" adjustment restriction on both limits of the range; 2- Could interfere with some rigid backrests; Not available with attendant lock and fixed carbon fiber side guards;
3- Only available with full length armrest; Not available with tubular (short and long) and short armrest; 4- Not available with attendant lock; 5- May have some restriction with seat-to-floor height and rear wheel

SIDE GUARDS (not available with Flip Back and "T" Armrest)				
SG01	☐	Plastic side guards (removable)		OTP
SG02	☐	Carbon fiber side guards (fixed)		OTP
SG03	☐	Carbon fiber side guards (removable)		OTP
SG06	☐	Plastic fender side guards - straight bracket (removable)		OTP
SG08	☐	Plastic fender side guards - offset bracket (removable) ¹		OTP
SG04	☐	Carbon fiber fender side guards (removable)		OTP
SG99	☐	Omit side guard		NC

1- only compatible with 0° camber; Increase distance between fender side guards by 1 1/8";

POSITIONING BELT							
SB01-S	☐	Velcro adjustable - Standard 35" ¹					OTP
SB01-L	☐	Velcro adjustable - Long 60"					OTP
SB02-S	☐	Auto buckle - Standard 35" ¹					NC
SB02-M	☐	Auto buckle - Medium 48"					NC
SB02-L		Auto buckle - Long 60"					NC
SB04-M	☐	BodyPoint Hip Belt - 2 point not padded - Medium 56"					OTP
SB04-L	☐	BodyPoint Hip Belt - 2 point not padded - Long 61"					OTP
SB05-S	☐	BodyPoint Hip Belt - 2 point padded - Small 51"					OTP
SB05-M	☐	BodyPoint Hip Belt - 2 point padded - Medium 56"					OTP
SB05-L	☐	BodyPoint Hip Belt - 2 point padded - Long 61"					OTP
SB06-S	☐	BodyPoint Hip Belt - 4 point padded - Small 51"					OTP
SB06-M	☐	BodyPoint Hip Belt - 4 point padded - Medium 56"					OTP
SB06-L	☐	BodyPoint Hip Belt - 4 point padded - Long 61"					OTP
SB03	☐	Hardware attachment for 2 extra points (1 pair)					OTP
SB08-M	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 18"					OTP
SB08-L	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 24"					OTP
SB99	☐	Omit positioning belt					NC

1- Not available with wheelchair width of 18" and more

HEADREST							
AC01-S	☐	Profiled Headrest - Small (3.5"X6")					OTP
AC01-M	☐	Profiled Headrest - Medium (4.5"X7")					OTP
AC01-L	☐	Profiled Headrest - Large (5.5"X8")					OTP
AC28	☐	Headrest mounting hardware with removable non folding stabilizer bar ¹					OTP

1- Only available with push handles - Not available with a stroller handle or a folding stabilizer bar


ACCESSORIES							
AC03	☒	Anti-tippers					NC
AC29	☐	Swing-away anti-tipper ¹	Left ☐	Right ☐			OTP
AC27	☐	Tip assist ²					OTP
AC06	☐	Cane and crutch holder	Left ☐	Right ☐			OTP
AC07	☐	Oxygen tank holder ⁴ - D and E Type - <i>Installed to the left</i>					OTP
AC08	☐	Spoke guards ³	Available: 20", 22", 24", 26"				OTP
AC09	☐	Footrest neoprene impact guard (<i>pair</i>) - Black					OTP
AC10	☐	Seat pouch					OTP
AC30	☐	Newton multi-purpose pouch					OTP
AC26	☐	BodyPoint Mobility Bag					OTP
AC23	☐	Newton Backpack					OTP
AC12	☐	Velcro Closing Strap					OTP
AC13	☐	Tool kit					OTP
AC16	☐	Motion Composites Polo Shirt	W/S ☐	W/M ☐	W/L ☐		OTP
			M/S ☐	M/M ☐	M/L ☐	M/XL ☐	M/XXL ☐
						M/XXXL ☐	

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 13 1/2" and 19 3/4"; Not available with amputee axle plate 2- Cannot be combined with Anti Tippers
3- Not available with Mag wheels and Spinergy; 4- Not compatible with swing away armrest, amputee axle plate and WC-19 transit tie-down

Colors																				
Options ¹	Black	Sunkissed Orange	Burgundy	Sapphire Blue	Monster Green	Charcoal	Fuchsia	Steel Blue	Ferrari Red	Acid Green	Electric Purple	Caribbean Blue	White	Pink Pearl	Plum Purple	Sky Blue	Black Cherry	Khaki Green (matte)	Desert Sand (matte)	
																				
AirGrip	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	OTP
Frame	☐																			NC

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

Fork and Stem bolt combinations



Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	1.25 to 2.75
	16	0.75 to 2.25
22 in	17+	0.75 to 2.75
	16	0.75 to 1.75
24 in	17	0.75 to 2.25
	18+	0.75 to 2.75



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the
EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The **EVO Custom Request Form** is the best place to start.

Note :