


1- Purchasing information

P.O. number:* _____ Date: _____

Company Name:* _____

Purchasing contact:* _____

Phone:* _____

Email:* _____

Contact preference:* Phone ☐ Email ☐

Marked for: _____

2- ATP/Clinician information

ATP/Clinician:* _____

Phone:* _____

Email:* _____

Contact preference:* Phone ☐ Email ☐

3- Shipping information

Ship to:* _____

Name: _____

Address: _____

City: _____ State: _____

Zip Code: _____

Phone: _____

MA083 ☐		MA084 ☐		MA085 ☐		MA086 ☐		MA087 ☐		MA088 ☐		MA089	
English Manual (STD)		German Manual		Italian Manual		Dutch Manual		Spanish Manual		French Manual		Portuguese Manual	
MODEL										USD (taxes not included)			
WC02	☐	Ultralight Helio A7 wheelchair 7000 series aluminum (120 kg/265 lb weight capacity)											\$2,575
WC09	☐	HD Heavy duty kit (159 kg/ 350 lb weight capacity)											\$540
WC10	☐	E-Motion adaptor Kit (2 adaptors) - Only necessary with 6° camber											\$35
Frame													
SEAT WIDTH ³ - cm (inches)													
SW	☐	35.56 (14") ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ¹ ☐	48.26 (19") ¹ ☐						NC
	☐	50.80 (20") ¹ ☐						53.34 (21") ² ☐	55.88 (22") ² ☐				\$535
SEAT DEPTH - cm (inches)													
SD	☐	35.56 (14") ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ☐	48.26 (19") ☐						NC
	☐	50.80 (20") ☐											\$515
TRANSIT TIE DOWN													
AC04	☐	Transit Tie Down (Unoccupied)											NC
AC05-S	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Short belt 50-104 cm (20" - 41")											\$365
AC05-L	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Long belt 50-116 cm (20" - 46")											\$365
AC35	☐	WC-19 Transit Tie Down without belt ⁴											\$335

1- Available with HD option; 2- Only available with HD option

[3. Width calculator](#)

4- May interfere with swing away armrest and Clamp on height adjustable push handle;



PACKAGES			
VP01	☐	Vision Package: Orange accent added to point of contact accessories including: footrest latches, "T" and flip back armrest button cap, 6" Push to lock extension and rubber inserts on Newton composite angle adjustable footplates ¹	\$95

1- Please select footplates, footrest, armrest, push to lock wheel lock and the extensions in the appropriate sections; To know the compatible parts, look for this logo ***VP01** ; Recommended with black chair;
See picture of the product on page 7.

A7 FRONT Seat-to-floor Height - Please select your choice

Forks / Position		3" caster			4" caster			5" caster			6" caster			7" caster			8" caster		
		Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length		
		STD	+ 2,54 cm 1"	+ 5,08cm 2"	STD	+ 2,54 cm 1"	+ 5,08cm 2"	STD	+ 2,54 cm 1"	+ 5,08cm 2"	STD	+ 2,54 cm 1"	+ 5,08cm 2"	STD	+ 2,54 cm 1"	+ 5,08cm 2"	STD	+ 2,54 cm 1"	+ 5,08cm 2"
4 in 10,2 cm	P1	33.02cm 13"	35.56cm 14"	38.10cm 15"	34.29cm 13.5"	36.83cm 14.5"	39.37cm 15.5"												
	P2	34.29cm 13.5"	36.83cm 14.5"	39.37cm 15.5"	35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"									
5 in 12,7 cm	P1																		
	P2				35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"									
	P3	35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"						
	P4	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"	40.64cm 16"	43.18cm 17"	45.72cm 18"	41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"			
7 in 17,8 cm	P1										41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"			
	P2							41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"			
	P3							43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"
	P4	41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"	48.26cm 19"	50.80cm 20"	53.3cm 21"
	P5	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"	48.26cm 19"	50.80cm 20"	53.3cm 21"	49.53cm 19.5"	52.07cm 20.5"	54.6cm 21.5"
Froglegs	P1				36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"												
	P2	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"									
	P3	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"	40.64cm 16"	43.18cm 17"	45.72cm 18"	41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"						

Height available +/- 0,65cm (1/4") (see stem bolt and fork combination at the end of the order form)

CASTERS				Availability		
CA01-03 to CA01-08	☐	Composite wheel w/ PU tire (1")		3", 4", 5", 6", 7", 8"		NC
CA10 to CA11	☐	Pneumatic casters (1 ¼")		6", 8"		\$175
CA14 to CA16	☐	Newton UltraCaster Composite (1 ½ ")		4", 5", 6"		\$98
CA17 to CA19	☐	Newton UltraCaster Aluminum (1 ½ ")		4", 5", 6"		\$198
CASTER OPTIONS						
CA12	☐	Caster Pin Locks (Available with +1" or +2" Stem bolt ONLY) ¹				\$320
CA13	☐	Carbon fiber Frog Legs suspension forks (Not available with caster pin locks)				\$515

1- Not Available with WC-19

A7 - REAR Seat-to-floor Height

WHEEL SIZES		Height available		Specify desired height: _____
☐	20" (451) wheel	31.75cm/12.5 "	to 43.81cm/17.25"	
☐	22" (501) wheel	34.29cm/13.5 "	to 46.35cm/18.25"	
☐	24" (540) wheel	36.83cm/14.5 "	to 48.89cm/19.25"	
☐	25" (559) wheel	38.10cm/15 "	to 50.16cm/19.75"	
☐	26" (590) wheel	39.37cm/15.5 "	to 51.34cm/20.25"	

Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- 1,25 cm (½") of selected Seat to Floor height"

Footrest						
SWING-IN/SWING-OUT FOOTREST						
FR03-01	☐	60° Swing-in/swing-out footrest	34.29 - 43.18cm (13.5" - 17")	Set at*:		NC
FR03-02	☐	60° Swing-in/swing-out footrest	36.83 - 49.53cm (14.5" - 19.5")	Set at*:		NC
FR03-03	☐	60° Swing-in/swing-out footrest	39.29 - 52.07cm (15.5" - 20.5")	Set at*:		NC
FR04-01	☐	70° Swing-in/swing-out footrest	34.29 - 43.18cm (13.5" - 17")	Set at*:		NC
FR04-02	☐	70° Swing-in/swing-out footrest	36.83 - 49.53cm (14.5" - 19.5")	Set at*:		NC
FR04-03	☐	70° Swing-in/swing-out footrest	39.37 - 52.07cm (15.5" - 20.5")	Set at*:		NC
FR15-01	☐	80° Swing-in/swing-out footrest ⁵	34.29 - 40.64cm (13.5" - 16")	Set at*:		NC
FR15-02	☐	80° Swing-in/swing-out footrest ⁵	36.83 - 49.53cm (14.5" - 19.5")	Set at*:		NC
FR15-03	☐	80° Swing-in/swing-out footrest ⁵	39.37 - 52.07cm (15.5" - 20.5")	Set at*:		NC
FR06	☐	90° swing-in/swing-out with front mount - Standard (no extension) ¹	19.05 - 27.94cm (7.5" - 11")	Set at*:		NC
FR07	☐	90° swing-in/swing-out with front mount - Short extension 2" ^{1, 2}	24.13 - 33.02cm (9.5" - 13")	Set at*:		NC
FR08	☐	90° swing-in/swing-out with front mount - Medium extension 4" ^{1, 2}	24.13 - 36.83cm (9.5" - 14.5")	Set at*:		NC
FOOTREST OPTIONS						
FR09	☐	High mount (<i>footplate attached to the hanger with clamps</i>) ³	12.70 - 34.29cm (5" - 13.5")	Set at*:		\$85
FR10	☐	Elevating legrest with calf pad, length adjustable ⁴	Left ☐ Right ☐	Set at:		\$248
FR99	☐	Omit Footrest				NC

1- Available only with two piece adjustable footplates; 2- May interfere with front casters; 3- Not available with front mount and the elevating legrest;

* +/- 1.27 cm (1/2")

4- The elevating legrest replace the footrest side selected; Not available with one piece footplate; 5- Not available with 8" caster

FOOTPLATES								
FP01	☐	Standard - Composite ¹						NC
FP02	☐	Newton adjustable angle - Composite ^{**VP01}						\$230
FP03	☐	Newton adjustable angle - Aluminum						\$255
FP04	☐	Newton adjustable angle - Carbon fiber with rubber inserts						\$450
FP23	☐	Newton adjustable angle extra deep - Aluminum						\$235
FP06	☐	One piece adjustable angle flip-up - Aluminum						\$205
FP07	☐	One piece adjustable angle flip-up - Carbon fiber with rubber inserts						\$470
FOOTPLATE ACCESSORIES								
FP08	☐	Length adjustable heel loop ²						\$45
FP09	☐	Calf strap						\$40
FP30	☐	Bodypoint Aeromesh Padded calf strap						\$125
1- Not available with front mount; 2- not available with one piece footplate								
SWING AWAY RESIDUAL LIMB SUPPORT								
FR27	☐	Residual limb support - flat 15.24x20.32cm (6"x8")	Left ☐	Right ☐				\$440
FR28	☐	Residual limb support - flat 20.32x24.4cm (8"x10")	Left ☐	Right ☐				\$440
FR29	☐	Residual limb support - flat 25.4x25.4cm (10"x10")	Left ☐	Right ☐				\$440
FR30	☐	Residual limb support - flat 25.4x35.56cm (10"x14")	Left ☐	Right ☐				\$440
FR32	☐	Residual limb support - contour 15.24x20.32cm (6"x8")	Left ☐	Right ☐				\$440
FR33	☐	Residual limb support - contour 20.32x24.4cm (8"x10")	Left ☐	Right ☐				\$440
Backrest								
FIXED ANGLE BACK CANES WITH INTEGRATED PUSH HANDLE (push handle included - no further selection needed)								
BC58-915	☐	Straight aluminum back cane	22.86 - 38.10cm (9" - 15")	increment of 1/2"	Set at ² :			NC
BC58-1521	☐	Straight aluminum back cane	38.10 - 53.34cm (15" - 21")	increment of 1/2"	Set at ² :			NC
BC60	☐	Straight aluminum back cane	53.34 - 60.96cm (21" - 24")	increment of 1"	Set at ² :			\$78
BC01-16	☐	8° bend aluminum back cane	40.64cm (16")					NC
BC01-18	☐	8° bend aluminum back cane	45.72cm (18")					NC
BC01-20	☐	8° bend aluminum back cane	50.08cm (20")					NC
BC59	☐	8° bend aluminum back cane	53.34 - 60.96cm (21" - 24")	increment of 1"	Set at ² :			\$78
FIXED ANGLE, HEIGHT ADJUSTABLE BACK CANES WITH PUSH HANDLE OPTIONS (MUST select ONE push handle options)								
BC11-912	☐	Straight aluminum back cane	22.86 - 30.48cm (9" - 12")	increment of 1/2"	Set at ² :			NC
BC11-1215	☐	Straight aluminum back cane	30.48 - 38.10cm (12" - 15")	increment of 1/2"	Set at ² :			NC
BC11-1518	☐	Straight aluminum back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ² :			NC
BC11-1821	☐	Straight aluminum back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ² :			NC
BC12-1315	☐	8° bend aluminum back cane	33.02 - 38.10cm (13.5" - 15")	increment of 1/2"	Set at ² :			NC
BC12-1518	☐	8° bend aluminum back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ² :			NC
BC12-1821	☐	8° bend aluminum back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ² :			NC
ANGLE AND HEIGHT ADJUSTABLE BACK CANE WITH PUSH HANDLE OPTIONS (MUST select ONE push handle options)								
BC13-1518	☐	Straight aluminum back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ² :			\$275
BC13-1821	☐	Straight aluminum back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ² :			\$275
BC14-1518	☐	8° bend aluminum back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ² :			\$275
BC14-1821	☐	8° bend aluminum back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ² :			\$275
		Select back cane angle:	85° ¹ ☐	90° ☐	95° STD ☐	100° ☐	105° ☐	110° ☐
PUSH HANDLES OPTIONS (ONE option at a time)								
PH01	☐	Push handles						STD
PH05	☐	Fold down push handles ^{3, 5}						\$140
PH06-920	☐	clamp on height adjustable push handles 22.86 - 50.8cm (9" - 20") ^{3, 4, 5}						\$330
PH06-923	☐	clamp on height adjustable push handles 22.86 - 58.4cm (9" - 23") ^{3, 4, 5}						\$330
PH02	☐	Omit push handles						NC
STROLLER HANDLE AND STABILIZER BAR (only available with push handle)								
PH04	☐	Stroller handle (not available with the HD option)						\$175
PH03	☐	Newton folding stabilizer bar (not available with stroller handle)						\$275
1- Not available with 8 degree bend cane; 2- If not indicated, default height setting is at the lowest position; measured from seat sling to top of back upholstery; 3- 265 lb weight limit; 4- Not compatible with swing away armrests, 8° bend back canes, 21-24" back canes and amputee axle plates; 5- Not compatible with stroller handle, the stabilizer bar, headrest and attendant lock								
BACK UPHOLSTERY								
BH07	☐	Slip-on Active-Mesh back upholstery						NC
BH08	☐	Adjustable tension Active-Mesh back upholstery						\$180
BH99	☐	Omit Back upholstery						STD
SEAT CUSHION								
SC01	☐	5.08 cm (2") Cushion						\$180
SC02	☐	7.62 cm (3") Cushion						\$200
SC99	☐	Omit seat cushion						STD

Rear wheels						
ONE ARM DRIVE ¹		Only available with Newton One rear wheels permanent axles, 0° camber				
HR22	☐	One arm drive - aluminum inner handrim ²	Left ☐	Right ☐		\$1,510
HR60	☐	One arm drive - plastic coated inner handrim ²	Left ☐	Right ☐		\$1,595
HR98	☐	Omit handrim on opposite side of the One Arm Drive (OAD)				NC
REAR WHEELS					Available	
RW01	☐	Mag ³			20", 22" 24"	\$57
RW02	☐	Newton One - spoke wheel ⁴			20", 22" 24"	NC
RW03	☐	Newton Gravity - ultralight wheel			20", 22", 24", 25", 26"	\$335
RW04	☐	Spinergy Spox	Blk STD ☐	Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐	22", 24", 25", 26"	\$865
RW05	☐	Spinergy LX	Blk STD ☐	Pur ⁵ ☐ Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐ Pink ⁵ ☐ Grn ⁵ ☐ Org ⁵ ☐	22", 24", 25", 26"	\$1,095
RW07	☐	Spinergy CLX ⁶	Blk STD ☐	Pur ⁵ ☐ Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐ Pink ⁵ ☐ Grn ⁵ ☐ Org ⁵ ☐	24", 25"	\$1,600
TIRES					Available	
AIRLESS						
TI01	☐	Soft Urethane 3.49cm (1 3/8") - Low Tread, black ⁹			20", 22" 24"	STD
TI02	☐	Soft Urethane 3.49cm (1 3/8") - Medium Tread, black ^{7,9}			22", 24", 25", 26"	\$105
TI04	☐	Soft Urethane 2.54cm (1") - No tread, black - <i>Shox</i>			22", 24", 25", 26"	\$125
TI08	☐	Pneumatic Airless insert 3.49cm (1 3/8") - Medium Tread ⁸			22", 24", 26"	\$90
PNEUMATIC						
TI05	☐	Pneumatic 3.49cm (1 3/8") Medium Tread ⁹			20", 22", 24", 25" 26"	NC
TI06	☐	Pneumatic HP 2.54cm (1") - Low Tread, Puncture resistant, black - <i>SpeedLite</i>			20", 22", 24", 25", 26"	\$110
TI07	☐	Pneumatic HP 2.54cm (1") - Medium Tread, Puncture resistant, black - <i>TrailBlazer</i>			24", 25", 26"	\$140
TI03	☐	Pneumatic 5.08cm (2") - Large Tread, black ¹⁰			22", 24", 25"	\$115

- 1- Offered with handrims on each side of the wheelchair; select the outer handrim in the handrims section; Only available with 24" wheel size; Not available with 21" and 22" wide;
2- Only standard handrim position available; 3- Not compatible with HP tires ; Only available with aluminum or plastic coated handrim, standard position; 4- Not compatible with Shox tires;
5- color spokes require an additionnal 10 days lead-time; 6- Only available with 1" tires; 7- 22" is only available with Mags and Newton One rear wheels;
8- Not available with Spinergy CLX, Spinergy LX 25", 26" and Spox 25", 26" rear wheels; 9- Not available with flip-back armrest when the 6° camber is selected;
10- Not available with armrests when the 3° or 6° camber are selected;

Handrims						
HANDRIM					Available	
HR01	☐	Aluminum anodized			20", 22", 24", 25", 26"	STD
HR61	☐	Aluminum black hard anodized ²			20", 22", 24", 25"	\$75
HR02	☐	Plastic coated ¹			20", 22", 24", 25", 26"	\$110
HR03	☐	High friction coated ^{1,2,3}			22", 24", 25", 26"	\$380
HR07-HR18 and HR65-HR71	☐	Newton Air Grip ² <i>See page 6 for the color selection and price</i>			20", 22", 24", 25", 26"	
HR28	☐	Surge ^{1,2,3,4} (1 1/2" Oval handrim w/ Gripton high friction strip)			22", 24", 25", 26"	\$425
HR05	☐	Surge LT ^{1,2,3,4} (1 1/8" Oval handrim w/ Gripton high friction strip)			22", 24", 25", 26"	\$465
HR04	☐	Natural Fit ^{1,2,3,4}			22", 24", 25", 26"	\$335
HR62	☐	Simi H ^{1,2,3} (1 3/8" Oval handrim with high friction strip)			22", 24", 25", 26"	\$395
HR63	☐	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)			22", 24", 25", 26"	\$425
HR64	☐	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)			22", 24", 25", 26"	\$325
HR99	☐	Omit handrim				NC

- 1- Only standard and narrow handrim position. By default, the tab won't be cut with the narrow position; 2- Not available with Mag wheels; 3 - Not available with one arm drive;
4- 25" and 26" are not available in narrow position; 24" is not available with the Spinergy Spox, LX and CLX in narrow position; CLX rear wheel are not available with thumb piece

Handrims option						
ASSEMBLY POSITION						
HR29	☐	Standard Handrim position	Full tab			STD
HR030	☐	Narrow Handrim position no cut	Full tab			NC
HR30	☐	Narrow Handrim position with cut ⁵	Short tab 2 positions			\$32
HR31	☐	Super Narrow Handrim ⁵	Short tab 2 positions STD ☐	Short tab 1 position ☐		\$32
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS						
HR23	☐	Standard grip				\$95
HR27	☐	Super grip				\$150
HR099	☐	Omit thumb piece				NC


- 5- Only available with Aluminum and Air Grip handrims;

AXLE						
AX01	☐	Quick release axle ¹				STD
AX02	☐	Permanent axle				NC
AX03	☐	Quad release axle ¹				\$135
AXLE PLATE						
AX04	☐	Amputee adjustable axle plate ²				\$210

- 1- Not required with one arm drive; 2 - May interfere with swing away armrest and limit seat to floor height; Not available with WC-19 transit tie down

REAR WHEEL CAMBER						
CM00	☐	0° camber				STD
CM03	☐	3° camber				NC
CM06	☐	6° camber (not available with amputee axle plate)				\$165

CENTER OF GRAVITY



Choose position of rear wheel axle plate:

Measure distance X from front of back post to center of axle receiver.

Most stable										Most responsive			
X =	AMPUTEE ¹	2,5 1"	3,2 1/4"	3,8 1/2"	4,4 3/4"	5,1 2"	5,7 1/4"	6,3 1/2"	7 3/4"	7,6 3"	8,3 1/4"	8,9 1/2"	9,5 3/4"
	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

If not indicated, default setting is at 3,8 cm (1.5")

Possible conflict between a seat depth under 40.6 cm (16") and a center of gravity over 6.3 cm (2.5").

Possible conflict between a 26" rear wheel and a center of gravity over 6.3 cm (2.5").

Motion Composites will select the closest possible center of gravity (COG) if an issue arises with the COG

1-Only available with the amputee axle plate

WHEEL LOCK							
WL08	☐	Newton Wheel lock - push to lock	PRODUCT IMPROVED				STD
WL16	☐	Aluminum push to lock with extensions					\$83
WL02	☐	Pull to lock					NC
WL04	☐	Newton grade aid push to lock (works best with pneumatic or high pressure tire)					\$165
WL13 WL14	☐	6" removable extension handle ¹ *VP01					\$83
WL05	☐	Scissors Lock					\$155
WL06	☐	Attendant Lock (additional set of wheel lock mounted to the back)					\$215
WL15	☐	Unilateral wheel lock - pull to lock ²	Left ☐	Right ☐			\$335
WL99	☐	Omit wheel locks					NC

1- Only available with Newton push to lock (WL08), pull to lock (WL02) and Newton Grade aid (WL04); Only the extension for the Newton push to lock is available with the vision package (VP01)

2- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:

https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

Armrests

HEIGHT ADJUSTABLE FLIP BACK ARMREST (Convertible to "T" armrest) ^{1,4} *VP01							
AR01-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐ Unlocked STD ☐			\$380
AR01-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐ Unlocked STD ☐			\$380
AR02-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐ Unlocked STD ☐			\$380
AR02-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐ Unlocked STD ☐			\$380
HEIGHT ADJUSTABLE "T" ARMREST ¹ *VP01							
AR13-610	☐	25.4cm (10") Desk length armpad ⁵	15.25 - 25.40cm (6" - 10")				\$350
AR03-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")				\$350
AR03-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")				\$350
AR14-610	☐	35.56cm (14") Full length armpad ⁵	15.25 - 25.40cm (6" - 10")				\$350
AR04-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")				\$350
AR04-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")				\$350
HEIGHT ADJUSTABLE SWING AWAY ARMREST ²							
AR05	☐	Tubular armrest - Short pad	20.32 - 27.94cm (8 - 11")				\$240
AR23	☐	Tubular armrest - Long pad	20.32 - 27.94cm (8 - 11")				\$240
AR06	☐	25.4cm (10") Desk Length flat armpad	20.32 - 27.94cm (8 - 11")				\$240
AR17	☐	35.56cm (14") Full Length flat armpad	20.32 - 27.94cm (8 - 11")				\$240
ARMREST OPTIONS							
AR12	☐	35.56cm (14") Full Length Armpad - Gel Ovation (pair) ³					\$165
AR99	☐	Omit armrest					NC

1- May have 1/2" adjustment restriction on both limits of the range; 2- Could interfere with some rigid backrests; Not available with attendant lock and fixed carbon fiber side guards;

3- Only available with full length armrest; Not available with swing away and desk length armrests; 4- Not available with attendant lock; 5- May have some restriction with seat-to-floor height and rear wheel

SIDE GUARDS (not available with Flip Back and "T" Armrest)							
SG01	☐	Plastic side guards (removable)	Straight bracket - STD	Offset bracket ¹			\$210
SG02	☐	Carbon fiber side guards (fixed)					\$275
SG03	☐	Carbon fiber side guards (removable)	Straight bracket - STD	Offset bracket ¹			\$315
SG06	☐	Plastic fender side guards (removable)	Straight bracket - STD	Offset bracket ¹			\$295
SG04	☐	Carbon fiber fender side guards (removable)	Straight bracket - STD	Offset bracket ¹			\$550
SG99	☐	Omit side guard					NC

1- only compatible with 0° camber; Increase width by 1/2" per side for a total of 1" ;

POSITIONING BELT							
SB01-S	☐	Velcro adjustable - Small 88.9cm (35") ¹					\$50
SB01-L	☐	Velcro adjustable - Long 152.40cm (60")					\$50
SB02-S	☐	Auto buckle - Small 88.9cm (35") ¹					\$95
SB02-M	☐	Auto buckle - Medium 121.92cm (48")					\$95
SB02-L	☐	Auto buckle - Long 152.40cm (60")					\$95
SB04-M	☐	BodyPoint Hip Belt - 2 point not padded - Medium 142.24cm (56")					\$95
SB04-L	☐	BodyPoint Hip Belt - 2 point not padded - Long 154.94cm (61")					\$95
SB05-S	☐	BodyPoint Hip Belt - 2 point padded - Small 129.54cm (51")					\$185
SB05-M	☐	BodyPoint Hip Belt - 2 point padded - Medium 142.24cm (56")					\$185
SB05-L	☐	BodyPoint Hip Belt - 2 point padded - Long 154.94cm (61")					\$185
SB06-S	☐	BodyPoint Hip Belt - 4 point padded - Small 129.54cm (51")					\$205
SB06-M	☐	BodyPoint Hip Belt - 4 point padded - Medium 142.24cm (56")					\$205
SB06-L	☐	BodyPoint Hip Belt - 4 point padded - Long 154.94cm (61")					\$205
SB03	☐	Hardware attachment for 2 extra points (1 pair)					\$17
SB08-M	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 73.66 (18")					\$310
SB08-L	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 93.98cm (24")					\$310
SB99	☐	Omit positioning belt					STD

1- Not recommended for seat width of 45.72cm (18") and more

HEADREST ¹							
AC01-S	☐	Profiled Headrest - Small 8.8x15.2cm (3.5"X6")					\$195
AC01-M	☐	Profiled Headrest - Medium 11.4x17.8cm (4.5"X7")					\$195
AC01-L	☐	Profiled Headrest - Large 14x2.3cm(5.5"X8")					\$195
AC28	☐	Headrest mounting hardware with removable non folding stabilizer bar ¹					\$320

1- Only available with push handles - Not available with a stroller handle or a folding stabilizer bar

ACCESSORIES							
AC03	☐	Anti-tippers					\$150
AC29	☐	Swing-away anti-tipper ¹	Left ☐	Right ☐			\$165
AC27	☐	Tip assist ²					\$67
AC06	☐	Cane and crutch holder	Left ☐	Right ☐			\$130
AC07	☐	Oxygen tank holder ⁴ - D and E Type - <i>Installed to the left</i>					\$335
AC08	☐	Spoke guards ³	Available: 20", 22", 24", 26"				\$125
AC09	☐	Footrest neoprene impact guard (<i>pair</i>) - Black					\$100
AC10	☐	Seat pouch					\$83
AC30	☐	Newton multi-purpose pouch					\$62
AC26	☐	BodyPoint Mobility Bag					\$135
AC23	☐	Newton Backpack					\$130
AC12	☐	Velcro Closing Strap					\$57
AC13	☐	Tool kit					\$50
AC16	☐	Motion Composites Polo Shirt	W/S ☐	W/M ☐	W/L ☐		\$36
			M/S ☐	M/M ☐	M/L ☐	M/XL ☐ M/XXL ☐ M/XXXL ☐	

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 34,3cm (13 1/2") and 50,2cm (19 3/4"); 2- Cannot be combined with Anti Tippers


3- Not available with Mag wheels and Spinergy; 4- Not compatible with swing away armrest, amputee axle plate and WC-19 transit tie-down

Colors																			
Options ¹																			
	Black	Sunkissed Orange	Burgundy	Sapphire Blue	Monster Green	Charcoal	Fuchsia	Steel Blue	Ferrari Red	Acid Green	Electric Purple	Caribbean Blue	White	Pink Pearl	Plum Purple	Sky Blue	Black Cherry	Khaki Green (matte)	Desert Sand (matte)
AirGrip	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Frame ²	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
FC99	☐	Custom Color Specify PPG Paintit color:																	additional 10 days lead-time
																			\$390

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

2- with black hydroformed aluminum crossbrace

Fork and Stem bolt combinations



Vision Package Accents



Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	1.5 to 3.75
	16	1.0 to 2.75
22 in	17	1.0 to 3.25
	18+	1.0 to 3.75
24 in	16	1.0 to 2.0
	17	1.0 to 2.75
	18+	1.0 to 3.75



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the
EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The **EVO Custom Request Form** is the best place to start.

Notes :