

3- Shipping information

Ship to:*	
Name:	
Address:	
City:	State:
Zip Code:	
Phone:	

ATP/Clinician:*			
Phone:*			
Email:*			
Contact preference:*	Phone ☐	Email ☐	* Required

MA083 ☐		MA084 ☐		MA085 ☐		MA086 ☐		MA087 ☐		MA088 ☐		MA089 ☐	
English Manual (STD)		German Manual		Italian Manual		Dutch Manual		Spanish Manual		French Manual		Portuguese Manual	
MODEL										USD (Taxes not included)			
WC05	☐	Ultralight Folding Carbon Fiber Helio C2 Wheelchair (120 kg - 265 lb weight capacity)											\$4,495
WC09	☐	HD Heavy Duty package (159 kg - 350 lb weight capacity)											\$540
WC10	☐	E-Motion adaptor Kit (2 adaptors) - Only necessary with 6° camber											\$35
Frame													
SEAT WIDTH ³ - cm (inches)													
SW	☐	35.56 (14") ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ¹ ☐	48.26 (19") ¹ ☐						NC
	☐			50.80 (20") ¹ ☐	53.34 (21") ² ☐	55.88 (22") ² ☐							\$535
SEAT DEPTH													
SD	☐	35.56 (14") ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ☐	48.26 (19") ☐						NC
	☐			50.80 (20") ☐									\$515
TRANSIT TIE DOWN													
AC04	☐	Transit Tie Down (Unoccupied)											NC
AC05-S	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴				Short belt 50-104 cm (20" - 41")						\$365	
AC05-L	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴				Long belt 50-116 cm (20" - 46")						\$365	
AC35	☐	WC-19 Transit Tie Down without belt ⁴											\$335

1- Available with HD option; 2- Only available with HD option

3. Width calculator

4- May interfere with swing away armrest and Clamp on height adjustable push handle; Not available with HD option



PACKAGES				
PK01	☐	Newton Ultralight Package (include: Carbon fiber angle adjustable footplates + Newton Gravity Ultralight rear wheels)	Save \$260	\$525
VP01	☐	Vision Package: Orange accent added to point of contact accessories including: footrest latches, "T" and flip back armrest button caps, 6" Push to lock extension and rubber inserts on Newton composite angle adjustable footplates ¹		\$95

1- Please select footplates, footrest, armrest, push to lock wheel lock and the extensions in the appropriate sections; To know the compatible parts, look for this logo ***VP01**; Recommended with black chair;
See picture of the product on page 6.

C2 FRONT Seat-to-floor Height - Please select your choice

		7.62cm (3") caster			10.16cm (4") caster			12.7cm (5") caster			15.24cm (6") caster			17.78cm (7") caster			20.32cm (8") caster		
		Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length			Stem bolt Length		
Forks / Position		STD	+ 2.54 cm 1"	+ 5.08cm 2"	STD	+ 2.54 cm 1"	+ 5.08cm 2"	STD	+ 2.54 cm 1"	+ 5.08cm 2"	STD	+ 2.54 cm 1"	+ 5.08cm 2"	STD	+ 2.54 cm 1"	+ 5.08cm 2"	STD	+ 2.54 cm 1"	+ 5.08cm 2"
4" 10.2 cm	P1	33.02cm 13"	35.56cm 14"	38.10cm 15"	34.29cm 14"	36.83cm 14.5"	39.37cm 15.5"												
	P2	34.29cm 13.5"	36.83cm 14.5"	39.37cm 15.5"	35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"									
5" 12.7 cm	P1																		
	P2				35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"									
	P3	35.56cm 14"	38.10cm 15"	40.64cm 16"	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"						
	P4	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"	40.64cm 16"	43.18cm 17"	45.72cm 18"	41.91cm 17.5"	44.45cm 18.5"	46.99cm 19.5"			
7" 17.8 cm	P1										41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"			
	P2							41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 18.5"	46.99cm 19.5"	49.53cm 20.5"			
	P3							43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"
	P4	41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"	50.80cm 20"	53.3cm 21"	
	P5	43.18cm 17"	45.72cm 18"	48.26cm 19"	44.45cm 17.5"	46.99cm 18.5"	49.53cm 19.5"	45.72cm 18"	48.26cm 19"	50.80cm 20"	46.99cm 18.5"	49.53cm 19.5"	52.07cm 20.5"	48.26cm 19"	50.80cm 20"	53.3cm 21"	49.53cm 19.5"	52.07cm 20.5"	54.6cm 21.5"
Froglegs	P1				36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"												
	P2	36.83cm 14.5"	39.37cm 15.5"	41.91cm 16.5"	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"									
	P3	38.10cm 15"	40.64cm 16"	43.18cm 17"	39.37cm 15.5"	41.91cm 16.5"	44.45cm 17.5"	40.64cm 16"	43.18cm 17"	45.72cm 18"	41.91cm 16.5"	44.45cm 17.5"	46.99cm 18.5"						

Height available +/- 0.65cm (1/4") (see stem bolt and fork combination at the end of the order form)

CASTERS				Available		
CA01-03 to CA01-08	☐	Composite wheel w/ PU tire (1")		3", 4", 5", 6", 7", 8"		NC
CA10 to CA11	☐	Pneumatic casters (1 1/4")		6", 8"		\$175
CA14 to CA16	☐	Newton UltraCaster Composite (1 1/2")		4", 5", 6"		\$98
CA17 to CA19	☐	Newton UltraCaster Aluminum (1 1/2")		4", 5", 6"		\$198
CASTER OPTIONS						
CA12	☐	Caster Pin Locks (Available with +1" or +2" Stem bolt ONLY) ¹				\$320
CA13	☐	Carbon fiber Frog Legs suspension forks (Not available with caster pin locks)				\$515

1- Not available with WC-19

C2 - REAR Seat-to-floor Height

WHEEL SIZES		Height available		Specify desired height: _____
☐	20" (451) wheel	31.75cm / 12.5"	to 43.81cm / 17.25"	
☐	22" (501) wheel	34.29cm / 13.5"	to 46.35cm / 18.25"	
☐	24" (540) wheel	36.83cm / 14.5"	to 48.89cm / 19.25"	
☐	25" (559) wheel	38.10cm / 15"	to 50.16cm / 19.75"	
☐	26" (590) wheel	39.37cm / 15.5"	to 51.34cm / 20.25"	

Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- 1cm" of selected seat to floor height"

Footrest						
SWING-IN/SWING-OUT FOOTREST						
FR03-01	☐	60° Swing-in/swing-out footrest - 34.29 - 43.18cm (13.5" - 17")		Set at*:		NC
FR03-02	☐	60° Swing-in/swing-out footrest - 36.83 - 49.53cm (14.5" - 19.5")		Set at*:		NC
FR03-03	☐	60° Swing-in/swing-out footrest - 39.29 - 52.07cm (15.5" - 20.5")		Set at*:		NC
FR04-01	☐	70° Swing-in/swing-out footrest - 34.29 - 43.18cm (13.5" - 17")		Set at*:		NC
FR04-02	☐	70° Swing-in/swing-out footrest - 36.83 - 49.53cm (14.5" - 19.5")		Set at*:		NC
FR04-03	☐	70° Swing-in/swing-out footrest - 39.37 - 52.07cm (15.5" - 20.5")		Set at*:		NC
FR15-01	☐	80° Swing-in/swing-out footrest - 34.29 - 40.64cm (13.5" - 16") ⁵		Set at*:		NC
FR15-02	☐	80° Swing-in/swing-out footrest - 36.83 - 49.53cm (14.5" - 19.5") ⁵		Set at*:		NC
FR15-03	☐	80° Swing-in/swing-out footrest - 39.37 - 52.07cm (15.5" - 20.5") ⁵		Set at*:		NC
FR06	☐	90° swing-in/swing-out with front mount - Standard (no extension) ¹	19.05 - 27.94cm (7.5" - 11")	Set at*:		NC
FR07	☐	90° swing-in/swing-out with front mount - Short extension 2" ^{1, 2}	24.13 - 33.02cm (9.5" - 13")	Set at*:		NC
FR08	☐	90° swing-in/swing-out with front mount - Medium extension 4" ^{1, 2}	24.13 - 36.83cm (9.5" - 14.5")	Set at*:		NC
FOOTREST OPTIONS ³						
FR09	☐	High mount (footplate attached to the hanger with clamps) ³	12.70 - 34.29cm (5" - 13.5")	Set at*:		\$85
FR10	☐	Elevating legrest with calf pad, length adjustable ⁴ Left ☐ Right ☐	35.56 - 55.88 cm (14"-22")	Set at:		\$248
FR99	☐	Omit Footrest				NC

1- Available only with two piece adjust. footplates; 2- May interfere with front casters; 3- Not available with front mount and the elevating legrest;

4- The elevating legrest replace the footrest side selected; Not available with one piece footplate; 5- Not available with 8" caster

FOOTPLATES						
FP01	☐	Standard - Composite ¹				NC
FP02	☐	Newton adjustable angle - Composite ^{**VP01}				\$230
FP03	☐	Newton adjustable angle - Aluminum				\$255
FP04	☐	Newton adjustable angle - Carbon fiber with rubber inserts				\$450
FP23	☐	Newton adjustable angle extra deep - Aluminum				\$235
FP06	☐	One piece adjustable angle flip-up - Aluminum				\$205
FP07	☐	One piece adjustable angle flip-up - Carbon fiber with rubber inserts				\$470
FOOTPLATE ACCESSORIES						
FP08	☐	Length adjustable heel loop ²				\$45
FP09	☐	Calf strap				\$40
FP30	☐	Bodypoint Aeromesh Padded calf strap				\$125

1- Not available with front mount; 2- not available with one piece footplate

SWING AWAY RESIDUAL LIMB SUPPORT						
FR27	☐	Residual limb support - flat 15.24x20.32cm (6"x8")	Left ☐	Right ☐		\$440
FR28	☐	Residual limb support - flat 20.32x24.4cm (8"x10")	Left ☐	Right ☐		\$440
FR29	☐	Residual limb support - flat 25.4x25.4cm (10"x10")	Left ☐	Right ☐		\$440
FR30	☐	Residual limb support - flat 25.4x35.56cm (10"x14")	Left ☐	Right ☐		\$440
FR32	☐	Residual limb support - contour 15.24x20.32cm (6"x8")	Left ☐	Right ☐		\$440
FR33	☐	Residual limb support - contour 20.32x24.4cm (8"x10")	Left ☐	Right ☐		\$440

Backrest						
FIXED ANGLE, HEIGHT ADJUSTABLE BACK CANES WITH PUSH HANDLE OPTIONS (MUST select ONE push handle options)						
BC06-912		Straight Carbon fiber back cane	22.86 - 30.48cm (9" - 12")	increment of 1/2"	Set at ²	NC
BC06-1215		Straight Carbon fiber back cane	30.48 - 38.10cm (12" - 15")	increment of 1/2"	Set at ²	NC
BC06-1518		Straight Carbon fiber back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ²	NC
BC06-1821		Straight Carbon fiber back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ²	NC
BC08-1315		8° Bend Carbon fiber back cane	34.29 - 38.1cm (13.5" - 15")	increment of 1/2"	Set at ²	\$60
BC08-1518		8° Bend Carbon fiber back cane	38.1 - 45.72cm (15" - 18")	increment of 1/2"	Set at ²	\$60
BC08-1821		8° Bend Carbon fiber back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ²	\$60
ANGLE AND HEIGHT ADJUSTABLE BACK CANE WITH PUSH HANDLE OPTIONS (MUST select ONE push handle options)						
BC09-1215	☐	Straight Carbon fiber back cane	30.48 - 38.10cm (12" - 15")	increment of 1/2"	Set at ²	\$220
BC09-1518	☐	Straight Carbon fiber back cane	38.10 - 45.72cm (15" - 18")	increment of 1/2"	Set at ²	\$220
BC09-1821	☐	Straight Carbon fiber back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ²	\$220
BC10-1315	☐	8° bend Carbon fiber back cane	34.29 - 38.1cm (13.5" - 15")	increment of 1/2"	Set at ²	\$275
BC10-1518	☐	8° bend Carbon fiber back cane	38.1 - 45.72cm (15" - 18")	increment of 1/2"	Set at ²	\$275
BC10-1821	☐	8° bend Carbon fiber back cane	45.72 - 53.34cm (18" - 21")	increment of 1/2"	Set at ²	\$275
		Select back cane angle:	85° ¹ ☐ 90° ☐ 95° STD ☐ 100° ☐ 105° ☐ 110° ☐			
PUSH HANDLES OPTIONS (ONE option at a time)						
PH01	☐	Push handles				STD
PH05	☐	Fold down push handles ^{3, 5}				\$140
PH06-920	☐	clamp on height adjustable push handles 22.86 -50.8cm (9" - 20") ^{3,4, 5}				\$330
PH06-923	☐	clamp on height adjustable push handles 22.86 - 58.4cm (9" - 23") ^{3,4, 5}				\$330
PH02	☐	Omit push handles				NC
STROLLER HANDLE AND STABILIZER BAR (only available with push handle)						
PH04	☐	Stroller handle (not available with the HD option)				\$175
PH03	☐	Newton folding stabilizer bar (not available with stroller handle)				\$275

1- Not available with 8 degree bend cane; 2- If not indicated, default height setting is at the lowest position; measured from seat sling to top of back upholstery; 3- 120kg (265 lb) weight limit

4- Not compatible with swing away armrests, 8° bend back canes and amputee axle plates; 5- Not compatible with stroller handle, stabilizer bar, headrest and attendant lock

BACK UPHOLSTERY						
BH07	☐	Slip-on Active-Mesh back upholstery				NC
BH08	☐	Adjustable tension Active-Mesh back upholstery				\$180
BH99	☐	Omit Back upholstery				STD
SEAT CUSHION						
SC01	☐	5.08 cm (2") Cushion				\$180
SC02	☐	7.62 cm (3") Cushion				\$200
SC99	☐	Omit seat cushion				STD

Rear wheels													
ONE ARM DRIVE ¹		Only available with Newton One rear wheels, permanent axles, 0° camber											
HR22	☐	One arm drive - aluminum inner handrim ²	Left ☐	Right ☐					\$1,510				
HR60	☐	One arm drive - plastic coated inner handrim ²	Left ☐	Right ☐					\$1,595				
HR98	☐	Omit handrim on opposite side of the One Arm Drive (OAD)							NC				
REAR WHEELS							Available						
RW01	☐	Mag ³					20", 22" 24"		\$57				
RW02	☐	Newton One - spoke wheel ⁴					20", 22" 24"		NC				
RW03	☐	Newton Gravity - ultralight wheel					20", 22", 24", 25", 26"		\$335				
RW04	☐	Spinergy Spox	Blk STD ☐	Wht ⁵ ☐	Blue ⁵ ☐	Red ⁵ ☐	Yel ⁵ ☐	22", 24", 25", 26"	\$865				
RW05	☐	Spinergy LX	Blk STD ☐	Pur ⁵ ☐	Wht ⁵ ☐	Blue ⁵ ☐	Red ⁵ ☐	Yel ⁵ ☐	Pink ⁵ ☐	Grn ⁵ ☐	Org ⁵ ☐	22", 24", 25", 26"	\$1,095
RW07	☐	Spinergy CLX ⁶	Blk STD ☐	Pur ⁵ ☐	Wht ⁵ ☐	Blue ⁵ ☐	Red ⁵ ☐	Yel ⁵ ☐	Pink ⁵ ☐	Grn ⁵ ☐	Org ⁵ ☐	24", 25"	\$1,600
TIRES							Available						
AIRLESS													
TI01	☐	Soft Urethane 3.49cm (1 3/8") - Low Tread, black ⁹					20", 22" 24"		STD				
TI02	☐	Soft Urethane 3.49cm (1 3/8") - Medium Tread, black ^{7,9}					22", 24", 25", 26"		\$105				
TI04	☐	Soft Urethane 2.54cm (1") - No tread, black - <i>Shox</i>					22", 24", 25", 26"		\$125				
TI08	☐	Pneumatic Airless insert 3.49cm (1 3/8") - Medium Tread ⁸					22", 24", 26"		\$90				
PNEUMATIC													
TI05	☐	Pneumatic 3.49cm (1 3/8") Medium Tread ⁹					20", 22", 24", 25", 26"		NC				
TI06	☐	Pneumatic HP 2.54cm (1") - Low Tread, Puncture resistant, black - <i>SpeedLite</i>					20", 22", 24", 25", 26"		\$110				
TI07	☐	Pneumatic HP 2.54cm (1") - Medium Tread, Puncture resistant, black - <i>TrailBlazer</i>					24", 25", 26"		\$140				
TI03	☐	Pneumatic 5.08cm (2") - Large Tread, black ¹⁰					22", 24", 25"		\$115				

Handrim					
HANDRIM			Available		
HR01	☐	Aluminum anodized	20", 22", 24", 25", 26"		STD
HR61	☐	Aluminum black hard anodized ²	20", 22", 24", 25"		\$75
HR02	☐	Plastic coated ¹	20", 22", 24", 25", 26"		\$110
HR03	☐	High friction coated ^{1,2,3}	22", 24", 25", 26"		\$380
HR07-HR18 and HR65-HR71	☐	Newton Air Grip ² <i>See on page 6 for color choice and price</i>	20", 22", 24", 25", 26"		
HR28	☐	Surge ^{1,2,3,4} (1 1/2" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26"		\$425
HR05	☐	Surge LT ^{1,2,3,4} (1 1/8" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26"		\$465
HR04	☐	Natural Fit ^{1,2,3,4}	22", 24", 25", 26"		\$335
HR62	☐	Simi H ^{1,2,3} (1 3/8" Oval handrim with high friction strip)	22", 24", 25", 26"		\$395
HR63	☐	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)	22", 24", 25", 26"		\$425
HR64	☐	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)	22", 24", 25", 26"		\$325
HR99	☐	Omit handrim			NC

Handrim option					
ASSEMBLY POSITION					
HR29	☐	Standard Handrim position	Full tab		STD
HR030	☐	Narrow Handrim position no cut	Full tab		NC
HR30	☐	Narrow Handrim position with cut ⁵	Short tab 2 positions		\$32
HR31	☐	Super Narrow Handrim ⁵	Short tab 2 positions STD ☐ Short tab 1 position ☐		\$32
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS					
HR23	☐	Standard grip			\$95
HR27	☐	Super grip			\$150
HR099	☐	Omit thumb piece			NC

AXLE ¹					
AX01	☐	Quick release axle ¹			STD
AX02	☐	Permanent axle			NC
AX03	☐	Quad release axle ¹			\$135
AXLE PLATE					
AX04	☐	Amputee adjustable axle plate ²			\$210

REAR WHEEL CAMBER						
CM00	☐	0° camber				STD
CM03	☐	3° camber				NC
CM06	☐	6° camber <i>(not available with amputee axle plate)</i>				\$165

Choose position of rear wheel axle plate:

Measure distance X from front of back post to center of axle receiver.

Most stable													
AMPUTEE ¹	2,5 1"	3,2 1/4"	3,8 1/2"	4,4 3/4"	5,1 2"	5,7 1/4"	6,3 1/2"	7 3/4"	7,6 3"	8,3 1/4"	8,9 1/2"	9,5 3/4"	10,1 4"
☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

If not indicated, default setting is at 3,8 cm/1.5"

Possible conflict between a seat depth under 40.6 cm (16") and a center of gravity over 6,3 cm (2,5").

Possible conflict between a 66 cm (26") rear wheel and a center of gravity over 6,3 cm (2,5").

Motion Composites will select the closest possible center of gravity (COG) if an issue arises with the COG

1-Only available with the amputee axle plate

WHEEL LOCK						
WL08	☐	Newton Wheel lock - push to lock		PRODUCT IMPROVED		STD
WL16	☐	Aluminum push to lock with extensions				\$83
WL02	☐	Pull to lock				NC
WL04	☐	Newton grade aid push to lock <i>(works best with pneumatic or high pressure tire)</i>				\$165
WL13	☐	6" removable extension handle ¹ *VP01				\$83
WL14	☐					
WL05	☐	Scissors Lock				\$155
WL06	☐	Attendant Lock <i>(additional set of wheel lock mounted to the back)</i>				\$215
WL15	☐	Unilateral wheel lock - pull to lock ²	Left ☐	Right ☐		\$335
WL99	☐	Omit wheel locks				NC

1- Only available with Newton push to lock (WL08), pull to lock (WL02) and Newton Grade aid (WL04); Only the extension for the Newton push to lock is available with the vision package (VP01)

2- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:

https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

Armrests						
HEIGHT ADJUSTABLE FLIP BACK ARMREST <i>(Convertible to "T" armrest)</i> ^{1,4} *VP01						
AR01-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐	Unlocked STD ☐	\$380
AR01-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐	Unlocked STD ☐	\$380
AR02-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐	Unlocked STD ☐	\$380
AR02-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐	Unlocked STD ☐	\$380
HEIGHT ADJUSTABLE "T" ARMREST ¹ *VP01						
AR13-610	☐	25.4cm (10") Desk length armpad ⁵	15.25 - 25.40cm (6" - 10")			\$350
AR03-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")			\$350
AR03-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")			\$350
AR14-610	☐	35.56cm (14") Full length armpad ⁵	15.25 - 25.40cm (6" - 10")			\$350
AR04-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")			\$350
AR04-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")			\$350
HEIGHT ADJUSTABLE SWING AWAY ARMREST ²						
AR05	☐	Tubular armrest - short pad	20.32 - 27.94cm (8 - 11")			\$240
AR23	☐	Tubular armrest - long pad	20.32 - 27.94cm (8 - 11")			\$240
AR06	☐	25.4cm (10") Desk Length flat armpad	20.32 - 27.94cm (8 - 11")			\$240
AR17	☐	35.56cm (14") Full Length flat armpad	20.32 - 27.94cm (8 - 11")			\$240
ARMREST OPTIONS						
AR12	☐	35.56cm (14") Full Length Armpad - Gel Ovation (pair) ³				\$165
AR99	☐	Omit armrest				NC

1- May have 1/2" adjustment restriction on both limits of the range; 2- Could interfere with some rigid backrests; Not available with attendant lock and fixed carbon fiber side guards;

3- Only available with full length armrest; Not available with swing away and desk length armrests; 4- Not available with attendant lock; 5- May have some restriction with seat-to-floor height and rear wheel

SIDE GUARDS <i>(not available with Flip Back and "T" Armrest)</i>						
SG01	☐	Plastic side guards <i>(removable)</i>	Straight bracket - STD	Offset bracket ¹		\$210
SG02	☐	Carbon fiber side guards <i>(fixed)</i>				\$275
SG03	☐	Carbon fiber side guards <i>(removable)</i>	Straight bracket - STD	Offset bracket ¹		\$315
SG06	☐	Plastic fender side guards <i>(removable)</i>	Straight bracket - STD	Offset bracket ¹		\$295
SG04	☐	Carbon fiber fender side guards <i>(removable)</i>	Straight bracket - STD	Offset bracket ¹		\$550
SG99	☐	Omit side guard				NC

1- only compatible with 0° camber;Increase width by 1/2" per side for a total of 1" ;


POSITIONING BELT					
SB01-S	☐	Velcro adjustable - Small 88.9cm (35") ¹			\$50
SB01-L	☐	Velcro adjustable - Long 152.40cm (60")			\$50
SB02-S	☐	Auto buckle - Small 88.9cm (35") ¹			\$95
SB02-M	☐	Auto buckle - Medium 121.92cm (48")			\$95
SB02-L	☐	Auto buckle - Long 152.40cm (60")			\$95
SB04-M	☐	BodyPoint Hip Belt - 2 point not padded - Medium 142.24cm (56")			\$95
SB04-L	☐	BodyPoint Hip Belt - 2 point not padded - Long 154.94cm (61")			\$95
SB05-S	☐	BodyPoint Hip Belt - 2 point padded - Small 129.54cm (51")			\$185
SB05-M	☐	BodyPoint Hip Belt - 2 point padded - Medium 142.24cm (56")			\$185
SB05-L	☐	BodyPoint Hip Belt - 2 point padded - Long 154.94cm (61")			\$185
SB06-S	☐	BodyPoint Hip Belt - 4 point padded - Small 129.54cm (51")			\$205
SB06-M	☐	BodyPoint Hip Belt - 4 point padded - Medium 142.24cm (56")			\$205
SB06-L	☐	BodyPoint Hip Belt - 4 point padded - Long 154.94cm (61")			\$205
SB03	☐	Hardware attachment for 2 extra points (1 pair)			\$17
SB08-M	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 73.66 (18")			\$310
SB08-L	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 93.98cm (24")			\$310
SB99	☐	Omit positioning belt			STD

1- Only available with push handles - Not available with a stroller handle or a folding stabilizer bar

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 34,3cm (13 1/2") and 50,2cm (19 3/4"); 2- Cannot be combined with

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

Fork and Stem bolt combinations



Vision Package Accents



Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	1.5 to 3.75
22 in	16	1.0 to 2.75
	17	1.0 to 3.25
	18+	1.0 to 3.75
24 in	16	1.0 to 2.0
	17	1.0 to 2.75
	18+	1.0 to 3.75



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the
EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The **EVO Custom Request Form** is the best place to start.

Notes :