



1- Purchasing information

P.O. number:* _____ Date: _____
 Company Name:* _____
 Purchasing contact:* _____
 Phone:* _____
 Email:* _____
 Contact preference:* Phone Email
 Marked for: _____

3- Shipping information

Ship to:* **Manitoba Wheelchair Program**
 Name: _____
 Address: **1857 Notre Dame Ave.**
 City: **Wpg** Province: **MB**
 Postal Code: **R3E 3E7**
 Phone: **204-975-3250**

NC = NO CHARGE (option available through Manitoba Possible)
 J = JUSTIFICATION REQUIRED (provide clinical rationale)
 OTP = OPTION TO PURCHASE (client responsible for cost)
 N/A = NOT AVAILABLE (option not available through Manitoba Possible)

MA080
 English Manual (STD)

Taxes not included

MODEL		Frame									
WC01	<input type="checkbox"/>	Ultraight MOVE wheelchair aluminum. (265 lb weight capacity)									NC
WC09	<input type="checkbox"/>	Heavy duty kit (350 lb weight capacity)									NC
SEAT WIDTH ³											
SW	<input type="checkbox"/>	14" <input type="checkbox"/>	15" <input type="checkbox"/>	16" <input type="checkbox"/>	17" <input type="checkbox"/>	18" ¹ <input type="checkbox"/>				NC	
	<input type="checkbox"/>	19" ¹ <input type="checkbox"/>	20" ¹ <input type="checkbox"/>	22" ² <input type="checkbox"/>						NC	
SEAT DEPTH											
SD	<input type="checkbox"/>	16" <input type="checkbox"/>			18" <input type="checkbox"/>					NC	
	<input type="checkbox"/>	20" <input type="checkbox"/>								NC	
TRANSIT TIE DOWN											
AC04	<input type="checkbox"/>	Transit Tie Down (Unoccupied)									NC
AC05-S	<input type="checkbox"/>	WC-19 Transit Tie Down w/Q'straint belt ⁴ Short belt 20"-41"									J
AC05-L	<input type="checkbox"/>	WC-19 Transit Tie Down w/Q'straint belt ⁴ Long belt 20"-46"									J
AC35	<input type="checkbox"/>	WC-19 Transit Tie Down without belt ⁴									J

1- Available with HD option; 2- Only available with HD option [3. Width calculator](#) 4- May interfere with swing away armrest and Clamp on height adjustable push handle; Not available with HD option

Move FRONT Seat-to-floor Height - Please select your choice

Fork/Position		4" caster (OTP)			5" caster (J)			6" caster (NC)			7" caster (OTP)			8" caster (NC)		
		Stem bolt length			Stem bolt length			Stem bolt length			Stem bolt length			Stem bolt length		
		STD	+1"	+2"												
4"	P1	12 1/2"	13 1/2"	14 1/2"												
	P2	13"	14"	15"		14 1/2"	15 1/2"									
5"	P1															
	P2	13"	14"	15"	13 1/2"	14 1/2"	15 1/2"									
	P3	13 1/2"	14 1/2"	15 1/2"	14"	15"	16"		15 1/2"	16 1/2"						
	P4	14"	15"	16"	14 1/2"	15 1/2"	16 1/2"	15"	16"	17"		16 1/2"	17 1/2"			
7"	P1							15 1/2"	16 1/2"	17 1/2"	16"	17"	18"			
	P2				15 1/2"	16 1/2"	17 1/2"	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"			
	P3				16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"
	P4	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"
	P5	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"	18 1/2"	19 1/2"	20 1/2"

Height available +/- 1/4" (see stem bolt and fork combination at the end of the order form); Orange boxes are not available with a seat slope of more than 1.5in.

FRONT CASTERS

CASTERS			Available
CA01-04 to CA01-08	<input type="checkbox"/>	Composite wheel w/ PU tire (1")	4", 5", 6", 7", 8"
CA10 to CA11	<input type="checkbox"/>	Pneumatic casters (1 ¼")	6", 8"
CA14 to CA16	<input type="checkbox"/>	Newton UltraCaster Composite (1 ½ ")	4", 5", 6"
CA17 to CA19	<input type="checkbox"/>	Newton UltraCaster Aluminum (1 ½ ")	4", 5", 6"

Move REAR Seat-to-floor Height - Please circle your choice

20" (451) (OTP)	22" (501) (NC)	24" (540) (NC)	25" (559) (OTP)	26" (590) (OTP)
12"	13"	14"	14 1/2"	15"
13"	14"	15"	15 1/2"	16"
14"	15"	16"	16 1/2"	17"
15"	16"	17"	17 1/2"	18"
16"	17"	18"	18 1/2"	19"
17"	18"	19"	19 1/2"	20"

Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- ½" of selected seat to floor height"

REAR WHEELS

ONE ARM DRIVE ¹			Only available with Newton One rear wheels, permanent axles, 0° camber		Available
HR22	<input type="checkbox"/>	One arm drive - aluminum inner handrim ^{2, 3}	24"	Left <input type="checkbox"/> Right <input type="checkbox"/>	J
HR60	<input type="checkbox"/>	One arm drive - plastic coated inner handrim ^{2, 3}	24"	Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
HR98	<input type="checkbox"/>	Omit handrim on opposite side of the One Arm Drive (OAD)			OTP
REAR WHEELS			Available		
RW01	<input type="checkbox"/>	Mag ⁴			20", 22" 24" OTP
RW02	<input type="checkbox"/>	Newton One - spoke wheel ⁵			20", 22" 24" NC
RW03	<input type="checkbox"/>	Newton Gravity - ultralight wheel			20", 22", 24", 25", 26" OTP
TIRES			Available		
Solid					
TI01	<input type="checkbox"/>	Soft Urethane 1 3/8"			20", 22" 24" NC
TI02	<input type="checkbox"/>	Soft Urethane knobby 1 3/8" ⁶			22", 24", 25", 26" OTP
TI04	<input type="checkbox"/>	Soft Urethane 1" - Shox			22", 24", 25", 26" OTP
Pneumatic					
TI05	<input type="checkbox"/>	Pneumatic 1 3/8"			20", 22", 24", 25", 26" NC
TI08	<input type="checkbox"/>	Pneumatic with Airless insert 1 3/8"			22", 24", 26" OTP
TI06	<input type="checkbox"/>	Pneumatic HP, Low Tread, Puncture resistant, black 1" - SpeedLite			20", 22", 24", 25", 26" OTP
TI07	<input type="checkbox"/>	Pneumatic HP, Medium Tread, Puncture resistant, black 1" - TrailBlazer			24", 25", 26" OTP

1- Offered with handrims on each side of the wheelchair; select the outer handrim in the handrims section; 2- Only standard handrim position available; 3- Not available with HD option

4- Not compatible with HP tires ; Only available with aluminum or plastic coated handrim in standard position; 5- Not compatible with Shox tires; 6- The 22" is only available with Mags and Newton One rear wheels

HANDRIMS

HANDRIM			Available
HR01	<input type="checkbox"/>	Aluminum anodized	20", 22", 24", 25", 26" NC
HR61	<input type="checkbox"/>	Aluminum black hard anodized ²	20", 22", 24", 25" OTP
HR02	<input type="checkbox"/>	Plastic coated ¹	20", 22", 24", 25", 26" OTP
HR03	<input type="checkbox"/>	High friction coated ^{1,2, 3}	22", 24", 25", 26" OTP
HR07-HR18 and HR65-HR71	<input type="checkbox"/>	Newton Air Grip ² <i>See page 5 for the color selection and price</i>	20", 22", 24", 25", 26" J
HR28	<input type="checkbox"/>	Surge ^{1,2,3} (1 1/2" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26" OTP
HR05	<input type="checkbox"/>	Surge LT ^{1,2,3} (1 1/8" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26" OTP
HR04	<input type="checkbox"/>	Natural Fit ^{1,2,3}	22", 24", 25", 26" OTP
HR62	<input type="checkbox"/>	Simi H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)	22", 24", 25", 26" OTP
HR63	<input type="checkbox"/>	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)	22", 24", 25", 26" OTP
HR64	<input type="checkbox"/>	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)	22", 24", 25", 26" OTP
HR99	<input type="checkbox"/>	Omit handrim	N/A

1- Only standard and narrow handrim position. By default, the tab won't be cut with the narrow position; 2- Not available with Mag wheels; 3 - Not available with one arm drive;

HANDRIMS OPTIONS


ASSEMBLY POSITION			Available
HR29	<input type="checkbox"/>	Standard Handrim position <i>Full tab</i>	NC
HR030	<input type="checkbox"/>	Narrow Handrim position no cut <i>Full tab</i>	J
HR30	<input type="checkbox"/>	Narrow Handrim position with cut ³ <i>Short tab 2 positions</i>	OTP
HR31	<input type="checkbox"/>	Super Narrow Handrim ³ <i>Short tab 2 positions STD</i> <input type="checkbox"/> <i>Short tab 1 position</i> <input type="checkbox"/>	J
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS			Available
HR23	<input type="checkbox"/>	Standard grip	OTP
HR27	<input type="checkbox"/>	Super grip	OTP
HR099	<input type="checkbox"/>	Omit thumb piece	NC

3- Only available with Aluminum and Air Grip handrims;

AXLES (0° camber) ¹			
AX01	<input type="checkbox"/>	Quick release axle	NC
AX02	<input type="checkbox"/>	Permanent axle	J
AX03	<input type="checkbox"/>	Quad release axle	OTP
AXLE PLATE			
AX04	<input type="checkbox"/>	Amputee adjustable axle plate ²	OTP

1- Not required with one arm drive 2 - May limit seat to floor height available

CENTER OF GRAVITY



Choose position of rear wheel axle plate:

Measure distance from front of back post to center of axle receiver.

Default setting is at 3/4"

Most stable	Most responsive
AMPUTEE ¹	3/4"
<input type="checkbox"/>	<input type="checkbox"/>
	2"
	<input type="checkbox"/>

1- Only available with amputee axle plate

WHEEL LOCKS

WL08	<input type="checkbox"/>	Newton Wheel lock - push to lock	NC
WL14	<input type="checkbox"/>	6" removable extension handle for push to lock	J
WL16	<input type="checkbox"/>	Aluminum push to lock with extensions	OTP
WL02	<input type="checkbox"/>	Pull to lock	OTP
WL04	<input type="checkbox"/>	Newton grade aid push to lock (<i>works best with pneumatic or high pressure tire</i>)	OTP
WL13	<input type="checkbox"/>	6" removable extension handle for pull to lock and grade aid	J
WL06	<input type="checkbox"/>	Attendant Lock (<i>additional set of wheel lock mounted to the back</i>)	OTP
WL15	<input type="checkbox"/>	Unilateral wheel lock - pull to lock ¹ Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
WL99	<input type="checkbox"/>	Omit wheel locks	N/A

1- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:

https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

FOOREST

SWING-AWAY FOOTREST

FR01-01	<input type="checkbox"/>	60° swing away footrest	13.5 - 17.5"	Set at:*	OTP
FR01-02	<input type="checkbox"/>	60° swing away footrest	15.5 - 19.5"	Set at:*	OTP
FR01-03	<input type="checkbox"/>	60° swing away footrest	17 - 21"	Set at:*	OTP
FR02-01	<input type="checkbox"/>	70° swing away footrest	13.5 - 17.5"	Set at:*	NC
FR02-02	<input type="checkbox"/>	70° swing away footrest	15.5 - 19.5"	Set at:*	NC
FR02-03	<input type="checkbox"/>	70° swing away footrest	17 - 21"	Set at:*	NC

FOOTREST OPTIONS

FR09	<input type="checkbox"/>	High mount (<i>footplate attached to the hanger with clamps</i>)	5" - 13.5"	Set at:*	J
FR10	<input type="checkbox"/>	Elevating legrest with calf pad, Length adjustable ¹ Left <input type="checkbox"/> Right <input type="checkbox"/>	14" - 22"	Set at:	J
FR99	<input type="checkbox"/>	Omit Footrest			J

1- The elevating legrest replace the footrest side selected; Not available with high mount

* +/- 1/2"

FOOTPLATES

FP01	<input type="checkbox"/>	Standard - Composite	NC
FP02	<input type="checkbox"/>	Newton adjustable angle - Composite	J
FP03	<input type="checkbox"/>	Newton adjustable angle - Aluminum	OTP

FOOTPLATE ACCESSORIES

FP08	<input type="checkbox"/>	Length adjustable heel loop	NC
FP09	<input type="checkbox"/>	Calf strap	OTP
FP30	<input type="checkbox"/>	Bodypoint Aeromesh Padded calf strap	OTP

SWING AWAY RESIDUAL LIMB SUPPORT

FR27	<input type="checkbox"/>	Residual limb support - flat 6"x8" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
FR28	<input type="checkbox"/>	Residual limb support - flat 8"x10" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
FR29	<input type="checkbox"/>	Residual limb support - flat 10"x10" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
FR30	<input type="checkbox"/>	Residual limb support - flat 10"x14" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
FR32	<input type="checkbox"/>	Residual limb support - contour 6"x8" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP
FR33	<input type="checkbox"/>	Residual limb support - contour 8"x10" Left <input type="checkbox"/> Right <input type="checkbox"/>	OTP

SEATING AND BACKREST

BACK UPHOLSTERY							
BH05	<input type="checkbox"/>	Slip-on Nylon back upholstery				NC	
BH06	<input type="checkbox"/>	Adjustable tension Nylon back upholstery				OTP	
BH99	<input type="checkbox"/>	Omit back upholstery				NC	
	<input type="checkbox"/>	NXT back Support		See pricelist		OTP	
SEAT CUSHIONS							
SC01	<input type="checkbox"/>	2" Cushion				OTP	
SC02	<input type="checkbox"/>	3" Cushion				OTP	
SC99	<input type="checkbox"/>	Omit seat cushion				NC	
	<input type="checkbox"/>	NXT cushion				OTP	
FIXED ANGLE BACK CANES WITH INTEGRATED PUSH HANDLE							
BC01-16	<input type="checkbox"/>	8° bend aluminum back cane	16"			NC	
BC01-18	<input type="checkbox"/>	8° bend aluminum back cane	18"			NC	
BC01-20	<input type="checkbox"/>	8° bend aluminum back cane	20"			NC	
BC59	<input type="checkbox"/>	8° bend aluminum back cane	21" - 24"	increment of 1"	Set at ² :	OTP	
ADJUSTABLE ANGLE BACK WITH INTEGRATED PUSH HANDLE							
BC02-16	<input type="checkbox"/>	8° bend aluminum back cane	16"			J	
BC02-20	<input type="checkbox"/>	8° bend aluminum back cane	20"			J	
		Select back cane angle:	90° <input type="checkbox"/>	95° STD <input type="checkbox"/>	100° <input type="checkbox"/>	105° <input type="checkbox"/>	110° <input type="checkbox"/>
STROLLER HANDLE AND STABILIZER BAR ¹							
PH04	<input type="checkbox"/>	Stroller handle (not available with the HD option)				OTP	
PH03	<input type="checkbox"/>	Newton folding stabilizer bar (not available with stroller handle)				OTP	

1- Stroller handle and stabilizer bar can't be combined 2- If not indicated, will be at the lowest position

ARMRESTS

HEIGHT ADJUSTABLE FLIP BACK ARMREST (Convertible to "T" armrest) ^{1,2}						
AR01-812	<input type="checkbox"/>	10" Desk length armpad	8" - 12"	Locked <input type="checkbox"/>	Unlocked STD <input type="checkbox"/>	NC
AR01-1014	<input type="checkbox"/>	10" Desk length armpad	10" - 14"	Locked <input type="checkbox"/>	Unlocked STD <input type="checkbox"/>	NC
AR02-812	<input type="checkbox"/>	14" Full length armpad	8" - 12"	Locked <input type="checkbox"/>	Unlocked STD <input type="checkbox"/>	NC
AR02-1014	<input type="checkbox"/>	14" Full length armpad	10" - 14"	Locked <input type="checkbox"/>	Unlocked STD <input type="checkbox"/>	NC
HEIGHT ADJUSTABLE "T" ARMREST ¹						
AR13-610	<input type="checkbox"/>	10" Desk length armpad ⁴	6" - 10"			NC
AR03-812	<input type="checkbox"/>	10" Desk length armpad	8" - 12"			NC
AR03-1014	<input type="checkbox"/>	10" Desk length armpad	10" - 14"			NC
AR14-610	<input type="checkbox"/>	14" Full length armpad ⁴	6" - 10"			NC
AR04-812	<input type="checkbox"/>	14" Full length armpad	8" - 12"			NC
AR04-1014	<input type="checkbox"/>	14" Full length armpad	10" - 14"			NC
ARMREST OPTIONS						
AR12	<input type="checkbox"/>	14" Full Length armpad - Gel Ovation (pair) ³				OTP
AR99	<input type="checkbox"/>	Omit armrest				NC

1- May have 1/2" adjust. restriction on both limits of the range; 2- Not available with attendant lock; 3- Not available with short flip back armrest and short "T" armrest;
4- May have restriction with seat-to-floor height and rear wheel

ACCESSORIES

POSITIONING BELTS						
SB01-S	<input type="checkbox"/>	Velcro adjustable - Standard 35" ¹				OTP
SB01-L	<input type="checkbox"/>	Velcro adjustable - Long 60"				OTP
SB02-S	<input type="checkbox"/>	Auto buckle - Standard 35" ¹				OTP
SB02-M	<input type="checkbox"/>	Auto buckle - medium 48"				OTP
SB02-L	<input type="checkbox"/>	Auto buckle - Long 60"				OTP
SB04-M	<input type="checkbox"/>	BodyPoint Hip Belt - 2 point not padded - Medium 56"				OTP
SB04-L	<input type="checkbox"/>	BodyPoint Hip Belt - 2 point not padded - Long 61"				OTP
SB05-S	<input type="checkbox"/>	BodyPoint Hip Belt - 2 point padded - Small 51"				OTP
SB05-M	<input type="checkbox"/>	BodyPoint Hip Belt - 2 point padded - Medium 56"				OTP
SB05-L	<input type="checkbox"/>	BodyPoint Hip Belt - 2 point padded - Long 61"				OTP
SB06-S	<input type="checkbox"/>	BodyPoint Hip Belt - 4 point padded - Small 51"				OTP
SB06-M	<input type="checkbox"/>	BodyPoint Hip Belt - 4 point padded - Medium 56"				OTP
SB06-L	<input type="checkbox"/>	BodyPoint Hip Belt - 4 point padded - Long 61"				OTP
SB03	<input type="checkbox"/>	Hardware attachment for 2 extra points (1 pair)				OTP
SB08-M	<input type="checkbox"/>	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 18"				OTP
SB08-L	<input type="checkbox"/>	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 24"				OTP
SB99	<input type="checkbox"/>	Omit positioning belt				NC

1- Not available with wheelchair width of 18" and more


ACCESSORIES			
AC03	<input checked="" type="checkbox"/>	Anti-tippers	NC
AC29	<input type="checkbox"/>	Swing-away anti-tipper ¹	Left <input type="checkbox"/> Right <input type="checkbox"/>
AC27	<input type="checkbox"/>	Tip assist ²	OTP
AC06	<input type="checkbox"/>	Cane and crutch holder	Left <input type="checkbox"/> Right <input type="checkbox"/>
AC07	<input type="checkbox"/>	Oxygen tank holder ⁴ - D and E Type - Installed to the left	OTP
AC08	<input type="checkbox"/>	Spoke guards ³	Available: 20", 22", 24", 26"
AC09	<input type="checkbox"/>	Footrest neoprene impact guard (pair) - Black	OTP
AC10	<input type="checkbox"/>	Seat pouch	OTP
AC30	<input type="checkbox"/>	Newton multi-purpose pouch	OTP
AC26	<input type="checkbox"/>	BodyPoint Mobility Bag	OTP
AC23	<input type="checkbox"/>	Newton Backpack	OTP
AC12	<input type="checkbox"/>	Velcro Closing Strap	OTP
AC13	<input type="checkbox"/>	Tool kit	OTP

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 13 1/2" and 19 3/4"; Not available with amputee axle plate; 2- Cannot be combined with Anti Tippers
3- Not available with Mag wheels and Spinergy; 4- Not compatible with swing away armrest, amputee axle plate and WC-19 transit tie-down

Colors																				
Options ¹	Black	Sunkissed Orange	Burgundy	Sapphire Blue	Monster Green	Charcoal	Fuchsia	Steel Blue	Ferrari Red	Acid Green	Electric Purple	Caribbean Blue	White	Pink Pearl	Plum Purple	Sky Blue	Black Cherry	Khaki Green (matte)	Desert Sand (matte)	
AirGrip	<input type="checkbox"/>	OTP																		
Frame	<input type="checkbox"/>																			NC

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

Fork and Stem bolt combinations



Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	2
	16	0.75 to 2
22 in	17+	0.75 to 2
	16	0.75
24 in	17	0.75 to 2
	18+	0.75 to 2



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The EVO Custom Request Form is the best place to start.

Notes :