



1- Purchasing information

P.O. number:* _____ Date: _____

Company Name:* _____

Purchasing contact:* _____

Phone:* _____

Email:* _____

Contact preference:* Phone ☐ Email ☐

Marked for: _____

3- Shipping information

Ship to:* **Manitoba Wheelchair Program**

Name: _____

Address: **1857 Notre Dame Ave.**

City: **Wpg** Province: **MB**

Postal Code: **R3E 3E7**

Phone: **204-975-3250**

NC = NO CHARGE (option available through Manitoba Possible)

J = JUSTIFICATION REQUIRED (provide clinical rationale)

OTP = OPTION TO PURCHASE (client responsible for cost)

N/A = NOT AVAILABLE (option not available through Manitoba Possible)

MA080 
 English Manual (STD)

Taxes not included

* Required		English Manual (STD)			Taxes not included	
MODEL						
WC01	☐	Ultralight MOVE wheelchair aluminum. (265 lb weight capacity)				NC
WC09	☐	Heavy duty kit (350 lb weight capacity)				NC
Frame						
SEAT WIDTH ³						
SW	☐	14" ☐	16" ☐	18" ¹ ☐		NC
	☐	20" ¹ ☐	22" ² ☐			NC
SEAT DEPTH						
SD	☐	16" ☐	18" ☐			NC
	☐	20" ☐				NC
TRANSIT TIE DOWN						
AC04	☐	Transit Tie Down (Unoccupied)				NC
AC05-S	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Short belt 20"-41"				J
AC05-L	☐	WC-19 Transit Tie Down w/Q'straint belt ⁴ Long belt 20"-46"				J
AC35	☐	WC-19 Transit Tie Down without belt ⁴				J

1- Available with HD option; 2- Only available with HD option [3. Width calculator](#) 4- May interfere with swing away armrest and Clamp on height adjustable push handle; Not available with HD option

Move FRONT Seat-to-floor Height - Please select your choice

Fork/Position		4" caster (OTP)			5" caster (J)			6" caster (NC)			7" caster (OTP)			8" caster (NC)		
		Stem bolt length			Stem bolt length			Stem bolt length			Stem bolt length			Stem bolt length		
		STD	+1"	+2"	STD	+1"	+2"	STD	+1"	+2"	STD	+1"	+2"	STD	+1"	+2"
4"	P1	12 1/2"	13 1/2"	14 1/2"												
	P2	13"	14"	15"		14 1/2"	15 1/2"									
5"	P1															
	P2	13"	14"	15"	13 1/2"	14 1/2"	15 1/2"									
	P3	13 1/2"	14 1/2"	15 1/2"	14"	15"	16"		15 1/2"	16 1/2"						
	P4	14"	15"	16"	14 1/2"	15 1/2"	16 1/2"	15"	16"	17"		16 1/2"	17 1/2"			
7"	P1							15 1/2"	16 1/2"	17 1/2"	16"	17"	18"			
	P2				15 1/2"	16 1/2"	17 1/2"	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"			
	P3				16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"
	P4	16"	17"	18"	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"
	P5	16 1/2"	17 1/2"	18 1/2"	17"	18"	19"	17 1/2"	18 1/2"	19 1/2"	18"	19"	20"	18 1/2"	19 1/2"	20 1/2"

Height available + - 1/4" (see stem bolt and fork combination at the end of the order form); Orange boxes are not available with a seat slope of more than 1.5in.

CASTERS				Available		
CA01-04 to CA01-08	☐	Composite wheel w/ PU tire (1")		4", 5", 6", 7", 8"		NC
CA10 to CA11	☐	Pneumatic casters (1 ¼")		6", 8"		OTP
CA14 to CA16	☐	Newton UltraCaster Composite (1 ½ ")		4", 5", 6"		OTP
CA17 to CA19	☐	Newton UltraCaster Aluminum (1 ½ ")		4", 5", 6"		OTP

Move REAR Seat-to-floor Height - Please circle your choice

20" (451) (OTP)	22" (501) (NC)	24" (540) (NC)	25" (559) (OTP)	26" (590) (OTP)
12"	13"	14"	14 1/2"	15"
13"	14"	15"	15 1/2"	16"
14"	15"	16"	16 1/2"	17"
15"	16"	17"	17 1/2"	18"
16"	17"	18"	18 1/2"	19"
17"	18"	19"	19 1/2"	20"

Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- ½" of selected seat to floor height"

Footrest						
SWING-AWAY FOOTREST						
FR01-01	☐	60° swing away footrest	13.5 - 17.5"	Set at:*		OTP
FR01-02	☐	60° swing away footrest	15.5 - 19.5"	Set at:*		OTP
FR01-03	☐	60° swing away footrest	17 - 21"	Set at:*		OTP
FR02-01	☐	70° swing away footrest	13.5 - 17.5"	Set at:*		NC
FR02-02	☐	70° swing away footrest	15.5 - 19.5"	Set at:*		NC
FR02-03	☐	70° swing away footrest	17 - 21"	Set at:*		NC
FOOTREST OPTIONS						
FR09	☐	High mount <i>(footplate attached to the hanger with clamps)</i>	5" - 13.5"	Set at:*		J
FR10	☐	Elevating legrest with calf pad, Length adjustable ¹	Left ☐ Right ☐ 14" - 22"	Set at:		J
FR99	☐	Omit Footrest				J

1- The elevating legrest replace the footrest side selected; Not available with high mount

* +/- 1/2"

FOOTPLATES						
FP01	☐	Standard - Composite				NC
FP02	☐	Newton adjustable angle - Composite				J
FP03	☐	Newton adjustable angle - Aluminum				OTP
FOOTPLATE ACCESSORIES						
FP08	☒	Length adjustable heel loop				NC
FP09	☐	Calf strap				OTP
FP30	☐	Bodypoint Aeromesh Padded calf strap				OTP

SWING AWAY RESIDUAL LIMB SUPPORT						
FR27	☐	Residual limb support - flat 6"x8"	Left ☐ Right ☐			OTP
FR28	☐	Residual limb support - flat 8"x10"	Left ☐ Right ☐			OTP
FR29	☐	Residual limb support - flat 10"x10"	Left ☐ Right ☐			OTP
FR30	☐	Residual limb support - flat 10"x14"	Left ☐ Right ☐			OTP
FR32	☐	Residual limb support - contour 6"x8"	Left ☐ Right ☐			OTP
FR33	☐	Residual limb support - contour 8"x10"	Left ☐ Right ☐			OTP

Backrest

FIXED ANGLE BACK CANES WITH INTEGRATED PUSH HANDLE

BC01-16	☐	8° bend aluminum back cane	16"			NC
BC01-18	☐	8° bend aluminum back cane	18"			NC
BC01-20	☐	8° bend aluminum back cane	20"			NC
BC59	☐	8° bend aluminum back cane	21" - 24"	increment of 1"	Set at ² :	OTP

ADJUSTABLE ANGLE BACK WITH INTEGRATED PUSH HANDLE

BC02-16	☐	8° bend aluminum back cane	16"			J	
BC02-20	☐	8° bend aluminum back cane	20"			J	
	Select back cane angle:		90° ☐	95° STD ☐	100° ☐	105° ☐	110° ☐

STROLLER HANDLE AND STABILIZER BAR ¹

PH04	☐	Stroller handle (not available with the HD option)				OTP
PH03	☐	Newton folding stabilizer bar (not available with stroller handle)				OTP

1- Stroller handle and stabilizer bar can't be combined

2- If not indicated, will be at the lowest position

BACK UPHOLSTERY

BH05	☐	Slip-on Nylon back upholstery				NC
BH06	☐	Adjustable tension Nylon back upholstery				OTP
BH99	☐	Omit back upholstery				NC
	☐	NXT back Support		See pricelist		OTP

SEAT CUSHIONS

SC01	☐	2" Cushion				OTP
SC02	☐	3" Cushion				OTP
SC99	☐	Omit seat cushion				NC
	☐	NXT cushion				OTP

Rear wheels

ONE ARM DRIVE ¹

Only available with Newton One rear wheels, permanent axles, 0° camber

HR22	☐	One arm drive - aluminum inner handrim ^{2, 3}	24"	Left ☐	Right ☐	J
HR60	☐	One arm drive - plastic coated inner handrim ^{2, 3}	24"	Left ☐	Right ☐	OTP
HR98	☐	Omit handrim on opposite side of the One Arm Drive (OAD)				OTP

REAR WHEELS

			Available		
RW01	☐	Mag ⁴	20", 22" 24"		OTP
RW02	☐	Newton One - spoke wheel ⁵	20", 22" 24"		NC
RW03	☐	Newton Gravity - ultralight wheel	20", 22", 24", 25", 26"		OTP

TIRES

			Available		
Solid					
TI01	☐	Soft Urethane 1 3/8"	20", 22" 24"		NC
TI02	☐	Soft Urethane knobby 1 3/8" ⁶	22", 24", 25", 26"		OTP
TI04	☐	Soft Urethane 1" - Shox	22", 24", 25", 26"		OTP
Pneumatic					
TI05	☐	Pneumatic 1 3/8"	20", 22", 24", 25", 26"		NC
TI08	☐	Pneumatic with Airless insert 1 3/8"	22", 24", 26"		OTP
TI06	☐	Pneumatic HP, Low Tread, Puncture resistant, black 1" - SpeedLite	20", 22", 24", 25", 26"		OTP
TI07	☐	Pneumatic HP, Medium Tread, Puncture resistant, black 1" - TrailBlazer	24", 25", 26"		OTP

1- Offered with handrims on each side of the wheelchair; select the outer handrim in the handrims section; 2- Only standard handrim position available; 3- Not available with HD option

4- Not compatible with HP tires ; Only available with aluminum or plastic coated handrim in standard position; 5- Not compatible with Shox tires; 6- The 22" is only available with Mags and Newton One rear wheels

Handrims

HANDRIM

			Available		
HR01	☐	Aluminum anodized	20", 22", 24", 25", 26"		NC
HR61	☐	Aluminum black hard anodized ²	20", 22", 24", 25"		OTP
HR02	☐	Plastic coated ¹	20", 22", 24", 25", 26"		OTP
HR03	☐	High friction coated ^{1,2, 3}	22", 24", 25", 26"		OTP
HR07-HR18 and HR65-HR71	☐	Newton Air Grip ²	20", 22", 24", 25", 26"		J
HR28	☐	Surge ^{1,2,3,4} (1 1/2" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26"		OTP
HR05	☐	Surge LT ^{1,2,3,4} (1 1/8" Oval handrim w/ Gripton high friction strip)	22", 24", 25", 26"		OTP
HR04	☐	Natural Fit ^{1,2,3,4}	22", 24", 25", 26"		OTP
HR62	☐	Simi H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)	22", 24", 25", 26"		OTP
HR63	☐	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)	22", 24", 25", 26"		OTP
HR64	☐	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)	22", 24", 25", 26"		OTP
HR99		Omit handrim			N/A

See page 5 for the color selection and price

1- Only standard and narrow handrim position. By default, the tab won't be cut with the narrow position; 2- Not available with Mag wheels; 3 - Not available with one arm drive;

4- 25" and 26" are not available in narrow position; 24" is not available with the Spinerigy Spox, LX and CLX in narrow position; CLX rear wheel are not available with thumb piece

MOVE Orderform Manitoba 6.3

February 5th, 2024

3 of 6

Handrims option						
ASSEMBLY POSITION						
HR29	☐	Standard Handrim position	Full tab			NC
HR030	☐	Narrow Handrim position no cut	Full tab			J
HR30	☐	Narrow Handrim position with cut ⁵	Short tab 2 positions			OTP
HR31	☐	Super Narrow Handrim ⁵	Short tab 2 positions STD ☐ Short tab 1 position ☐			J
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS						
HR23	☐	Standard grip				OTP
HR27	☐	Super grip				OTP
HR099	☐	Omit thumb piece				NC


5- Only available with Aluminum and Air Grip handrims;

AXLES (0° camber) ¹						
AX01	☐	Quick release axle				NC
AX02	☐	Permanent axle				J
AX03	☐	Quad release axle				OTP
AXLE PLATE						
AX04	☐	Amputee adjustable axle plate ²				OTP

1- Not required with one arm drive

2 - May limit seat to floor height available

CENTER OF GRAVITY



Choose position of rear wheel axle plate:

Measure distance from front of back post to center of axle receiver.
Default setting is at 3/4"

Most stable

Most responsive

AMPUTEE ¹

3/4"

2"

☐

☐

☐

1- Only available with amputee axle plate

WHEEL LOCKS						
WL08	☐	Newton Wheel lock - push to lock	PRODUCT IMPROVED			NC
WL14	☐	6" removable extension handle for push to lock				J
WL16	☐	Aluminum push to lock with extensions				OTP
WL02	☐	Pull to lock				J
WL04	☐	Newton grade aid push to lock (works best with pneumatic or high pressure tire)				OTP
WL13	☐	6" removable extension handle for pull to lock and grade aid				J
WL06	☐	Attendant Lock (additional set of wheel lock mounted to the back)				OTP
WL15	☐	Unilateral wheel lock - pull to lock ¹	Left ☐ Right ☐			OTP
WL99	☐	Omit wheel locks				N/A

1- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:

https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

Armrests						
HEIGHT ADJUSTABLE FLIP BACK ARMREST (Convertible to "T" armrest) ^{1,2}						
AR01-812	☐	10" Desk length armpad	8" - 12"	Locked ☐ Unlocked STD ☐		NC
AR01-1014	☐	10" Desk length armpad	10" - 14"	Locked ☐ Unlocked STD ☐		NC
AR02-812	☐	14" Full length armpad	8" - 12"	Locked ☐ Unlocked STD ☐		NC
AR02-1014	☐	14" Full length armpad	10" - 14"	Locked ☐ Unlocked STD ☐		NC
HEIGHT ADJUSTABLE "T" ARMREST ¹						
AR13-610	☐	10" Desk length armpad ⁴	6" - 10"			NC
AR03-812	☐	10" Desk length armpad	8" - 12"			NC
AR03-1014	☐	10" Desk length armpad	10" - 14"			NC
AR14-610	☐	14" Full length armpad ⁴	6" - 10"			NC
AR04-812	☐	14" Full length armpad	8" - 12"			NC
AR04-1014	☐	14" Full length armpad	10" - 14"			NC
ARMREST OPTIONS						
AR12	☐	14" Full Length armpad - Gel Ovation (pair) ³				OTP
AR99	☐	Omit armrest				NC

1- May have 1/2" adjust. restriction on both limits of the range; 2- Not available with attendant lock; 3- Not available with short flip back armrest and short "T" armrest;

4- May have restriction with seat-to-floor height and rear wheel

POSITIONING BELTS							
SB01-S	☐	Velcro adjustable - Standard 35" ¹					OTP
SB01-L	☐	Velcro adjustable - Long 60"					OTP
SB02-S	☐	Auto buckle - Standard 35" ¹					NC
SB02-M		Auto buckle - Medium 48"					NC
SB02-L	☐	Auto buckle - Long 60"					NC
SB04-M	☐	BodyPoint Hip Belt - 2 point not padded - Medium 56"					NC
SB04-L	☐	BodyPoint Hip Belt - 2 point not padded - Long 61"					OTP
SB05-S	☐	BodyPoint Hip Belt - 2 point padded - Small 51"					OTP
SB05-M	☐	BodyPoint Hip Belt - 2 point padded - Medium 56"					OTP
SB05-L	☐	BodyPoint Hip Belt - 2 point padded - Long 61"					OTP
SB06-S	☐	BodyPoint Hip Belt - 4 point padded - Small 51"					OTP
SB06-M	☐	BodyPoint Hip Belt - 4 point padded - Medium 56"					OTP
SB06-L	☐	BodyPoint Hip Belt - 4 point padded - Long 61"					OTP
SB03	☐	Hardware attachment for 2 extra points (1 pair)					OTP
SB08-M	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 18"					OTP
SB08-L	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 24"					OTP
SB99	☐	Omit positioning belt					NC

1- Not available with wheelchair width of 18" and more

ACCESSORIES								
AC03	☒	Anti-tippers						NC
AC29	☐	Swing-away anti-tipper ¹	Left ☐	Right ☐				OTP
AC27	☐	Tip assist ²						OTP
AC06	☐	Cane and crutch holder	Left ☐	Right ☐				OTP
AC07	☐	Oxygen tank holder ⁴ - D and E Type - Installed to the left						OTP
AC08	☐	Spoke guards ³	Available: 20", 22", 24", 26"					OTP
AC09	☐	Footrest neoprene impact guard (<i>pair</i>) - Black						OTP
AC10	☐	Seat pouch						OTP
AC30	☐	Newton multi-purpose pouch						OTP
AC26	☐	BodyPoint Mobility Bag						OTP
AC23	☐	Newton Backpack						OTP
AC12	☐	Velcro Closing Strap						OTP
AC13	☐	Tool kit						OTP
AC16	☐	Motion Composites Polo Shirt	W/S ☐	W/M ☐	W/L ☐			OTP
			M/S ☐	M/M ☐	M/L ☐	M/XL ☐	M/XXL ☐	M/XXXL ☐

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 13 1/2" and 19 3/4" ; Not available with amputee axle plate


2- Cannot be combined with Anti Tippers

3- Not available with Mag wheels and Spinergy; 4- Not compatible with swing away armrest, amputee axle plate and WC-19 transit tie-down

Colors																				
Options ¹	Black	Sunkissed Orange	Burgundy	Sapphire Blue	Monster Green	Charcoal	Fuchsia	Steel Blue	Ferrari Red	Acid Green	Electric Purple	Caribbean Blue	White	Pink Pearl	Plum Purple	Sky Blue	Black Cherry	Khaki Green (matte)	Desert Sand (matte)	
																				
AirGrip	☐ J	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	OTP
Frame	☐																			NC

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

Fork and Stem bolt combinations



Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	2
22 in	16	0.75 to 2
	17+	0.75 to 2
24 in	16	0.75
	17	0.75 to 2
	18+	0.75 to 2



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the
EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The **EVO Custom Request Form** is the best place to start.

Notes :