


VELOCE
ORDER FORM - INTERNATIONAL
1- Purchasing information

P.O. number:* _____ Date: _____
Company Name:* _____
Purchasing contact:* _____
Phone:* _____
Email:* _____
Contact preference:* Phone ☐ Email ☐
Marked for: _____

3- Shipping information

Ship to:* _____
Name: _____
Address: _____
City: _____ State: _____
Zip Code: _____
Phone: _____

2- ATP/Clinician information

ATP/Clinician:* _____
Phone:* _____
Email:* _____
Contact preference:* Phone ☐ Email ☐ * Required

MA083 ☐ MA084 ☐ MA085 ☐ MA086 ☐ MA087 ☐ MA088 ☐ MA089 ☐
English Manual (STD) German Manual Italian Manual Dutch Manual Spanish Manual French Manual Portuguese Manual

MODEL								USD (Taxes not included)		
WC20		☐	Ultralight VELOCE Wheelchair (120 kg - 265 lb weight limit)							\$5,295
WC09		☐	HD Heavy Duty package (159 kg - 350 lb weight capacity)							\$540
WC10		☐	E-Motion adaptor Kit (2 adaptors) - Only necessary with 6" camber							\$35
Frame										
SEAT WIDTH ³ - cm (inches)										
SW	☐	35.56 (14") ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ² ☐	48.26 (19") ² ☐			NC
	☐	50.80 (20") ² ☐					53.34 (21") ² ☐	55.88 (22") ² ☐		
SEAT DEPTH - cm (inches)										
SD	☐	35.56 (14") ¹ ☐	38.10 (15") ☐	40.64 (16") ☐	43.18 (17") ☐	45.72 (18") ☐	48.26 (19") ☐			NC
	☐	50.80 (20") ☐								
FRAME LENGTH (Seat sling depth plus distance from seat sling to front of frame) ⁴										
SP01	☐	Standard frame length configuration ⁵								STD
SP02	☐	Frame length 2.54 cm (1") longer than standard configuration								NC
SP03	☐	Frame length 5.08 cm (2") longer than standard configuration								NC
SP04	☐	Frame length 2.54 cm (1") shorter than standard configuration								NC
SP05	☐	Frame length 5.08 cm (2") shorter than standard configuration								NC
TRANSIT TIE DOWN										
AC05-S	☐	WC-19 Transit Tie Down w/Q'straint belt ⁶			Short belt 50-104 cm (20" - 41")					\$365
AC05-L	☐	WC-19 Transit Tie Down w/Q'straint belt ⁶			Long belt 50-116 cm (20" - 46")					\$365
AC35	☐	WC-19 Transit Tie Down without belt ⁶								\$335

1- Only available with frame length 1" and 2" longer; 2- Available with HD option; When HD option is selected, only the one piece angle adjustable flip-up footplate is available;

4- See chart on page 7; 5- 4.375" from seat sling to front frame; 6- May interfere with swing away armrest and Clamp on height adjustable push handle; Not available with HD option;

7- Only available with HD option and the one piece adjustable angle flip-up


[3. Width calculator](#)

FRONT Seat-to-floor height

Caster sizes	Height available +/- 1/4"	Specify desired height: (inches)
☐ 3" Caster	35.56cm to 53.34cm (14" to 21")	
☐ 4" Caster	36.83cm to 53.34cm (14.5" to 21")	
☐ 5" Caster	39.37cm to 53.34cm (15.5" to 21")	
☐ 6" Caster	41.91cm to 53.34cm (16.5" to 21") (N/A with 90° front frame)	

Frog Legs FRONT Seat-to-floor height

Caster Sizes	Height available +/- 1/4"	Specify desired height: (inches)
☐ 3" Caster	38.7cm to 53.3cm (15.25" to 21")	
☐ 4" Caster	40.0cm to 53.3cm (15.75" to 21")	
☐ 5" Caster	42.54cm to 53.3cm (16.75" to 21")	
☐ 6" Caster	45.08cm to 53.3cm (17.75" to 21") (N/A with 90° front frame)	




CASTERS				Availability		
CA01-03 to CA01-06	☐	Composite wheel w/ PU tire (1")		3", 4", 5", 6"		NC
CA10	☐	Pneumatic casters (1 ¼")		6"		\$175
CA14 to CA16	☐	Newton UltraCaster Composite (1 ½ ")		4", 5", 6"		\$98
CA17 to CA19	☐	Newton UltraCaster Aluminum (1 ½ ")		4", 5", 6"		\$198
CASTER OPTIONS						
CA13	☐	Carbon fiber Frog Legs suspension forks				\$515

REAR Seat-to-floor Height

WHEEL SIZES		Height available	Specify desired height: (inches)
☐	22" (501) wheel	34.29cm to 46.35cm (13.5" to 18.25")	
☐	24" (540) wheel	36.83cm to 48.89cm (14.5" to 19.25")	
☐	25" (559) wheel	38.10cm to 50.16cm (15" to 19.75")	
☐	26" (590) wheel	39.37cm to 51.43cm (15.5" to 20.25")	

Configuration used: 2.5 cm (1") seat slope with a center of gravity at 5cm (2")


Note: Tire size, center of gravity setting and seat slope may result in a variation of +/- 1,25 cm (½") of selected Seat to Floor height"

FRONT FRAME ANGLE						
FA70	☐	70° Front frame angle				NC
FA75	☐	75° Front frame angle				NC
FA80	☐	80° Front frame angle				NC
FA85	☐	85° Front frame angle				NC
FA90	☐	90° Front frame angle				NC


SEAT TO FOOTREST LENGTH						
-------------------------	--	--	--	--	--	--

Set Length to¹: Length must be at least 4,5 cm (1 ¼") shorter than front seat-to-floor height

1 - +/- 1.27 cm (1/2")



Footrest width / Taper selection			
Seat Width		Straight ¹	1" Taper
Outside Measurement		6,4 cm Narrower than Seat Width	11,4 cm Narrower than Seat Width
35.56	14"	29.21cm/11.5"	24.13cm/9.5"
38.10	15"	31.75cm/12.5"	26.67cm/10.5"
40.64	16"	34.29cm/13.5"	29.21cm/11.5"
43.18	17"	36.83cm/14.5"	31.75cm/12.5"
45.72	18"	39.37cm/15.5"	34.29cm/13.5"
48.26	19"	41.91cm/16.5"	36.83cm/14.5"
50.80	20"	44.45cm/17.5"	39.37cm/15.5"
53.34	21"	46.99cm/18.5"	41.91cm/16.5"
55.88	22"	49.53cm/19.5"	44.45cm/17.5"



1- Not compatible with auto-folding footplate

FOOTPLATES						
FP06	☐	One piece adjustable angle flip-up - Aluminum				NC
FP07	☐	One piece adjustable angle flip-up - Carbon fiber with rubber inserts				\$570
FP28	☐	One piece auto-folding adjustable angle - Aluminum				\$310
FP29	☐	One piece auto-folding adjustable angle - Carbon fiber with rubber inserts				\$380

FOOTPLATE ACCESSORIES						
FP09	☐	Calf strap				\$40
FP30	☐	Bodypoint Aeromesh Padded calf strap				\$125

Backrest							
HEIGHT ADJUSTABLE WITH PUSH HANDLES (MUST select ONE push handle options)							
BC06-912	☐	Straight Carbon fiber back cane	22.86 - 30.48cm (9-12")	increment of 1/2"	Set at ² :		NC
BC06-1215	☐	Straight Carbon fiber back cane	30.48 - 38.10cm (12-15")	increment of 1/2"	Set at ² :		NC
BC06-1518	☐	Straight Carbon fiber back cane	38.10 - 45.72cm (15-18")	increment of 1/2"	Set at ² :		NC
BC06-1821	☐	Straight Carbon fiber back cane	45.72 - 53.37cm (18-21")	increment of 1/2"	Set at ² :		NC
BC08-1315	☐	8° Bend Carbon fiber back cane	34.29 - 38.10cm (13 ½-15")	increment of 1/2"	Set at ² :		\$60
BC08-1518	☐	8° Bend Carbon fiber back cane	38.10 - 45.72 (15-18")	increment of 1/2"	Set at ² :		\$60
BC08-1821	☐	8° Bend Carbon fiber back cane	45.72 - 53.34cm (18-21")	increment of 1/2"	Set at ² :		\$60
ANGLE AND HEIGHT ADJUSTABLE BACK CANE WITH PUSH HANDLE OPTIONS (MUST select ONE push handle options)							
BC09-1215	☐	Straight Carbon fiber back cane	30.48 - 38.10cm (12-15")	increment of 1/2"	Set at ² :		\$220
BC09-1518	☐	Straight Carbon fiber back cane	38.10 - 45.72cm (15-18")	increment of 1/2"	Set at ² :		\$220
BC09-1821	☐	Straight Carbon fiber back cane	45.72 - 53.37cm (18-21")	increment of 1/2"	Set at ² :		\$220
BC10-1315	☐	8° bend Carbon fiber back cane	34.29 - 38.10cm (13 ½-15")	increment of 1/2"	Set at ² :		\$275
BC10-1518	☐	8° bend Carbon fiber back cane	38.10 - 45.72 (15-18")	increment of 1/2"	Set at ² :		\$275
BC10-1821	☐	8° bend Carbon fiber back cane	45.72 - 53.34cm (18-21")	increment of 1/2"	Set at ² :		\$275
		Select back cane angle:	85° ¹ ☐ 90° ☐ 95° STD ☐ 100° ☐ 105° ☐ 110° ☐				
PUSH HANDLES OPTIONS (ONE option at a time)							
PH01	☐	Push handles					NC
PH05	☐	Fold down push handles ^{3, 5}					\$140
PH06-920	☐	Clamp on height adjustable push handles 22.86 -50.80cm (9" - 20") ^{3,4, 5}					\$330
PH06-923	☐	Clamp on height adjustable push handles 22.86 - 58.4cm (9" - 23") ^{3,4, 5}					\$330
PH02	☐	Omit push handles					NC
¹ - Not available with a 8° bend back cane; ² - If notindicated, default height setting is at the lowest position; measured from seat sling to top of back upholstery; ³ - 120 kg/265lb weight limit ⁴ - Not compatible with swing away armrests, 8° bend back canes; ⁵ - Not compatible with headrest and attendant lock							
BACK UPHOLSTERY							
BH07	☐	Slip-on Active-Mesh back upholstery					NC
BH08	☐	Adjustable tension Active-Mesh back upholstery					\$180
BH99	☐	Omit Back upholstery					NC
SEAT CUSHION							
SC01	☐	5.08 cm (2") Cushion					\$180
SC02	☐	7.62 cm (3") Cushion					\$200
SC99	☐	Omit seat cushion					STD

Rear wheels						
ONE ARM DRIVE ¹		Only available with Newton One rear wheels, permanent axles, 0° camber				
HR22	☐	One arm drive - aluminum inner handrim ²	Left ☐	Right ☐		\$1,510
HR60	☐	One arm drive - plastic coated inner handrim ²	Left ☐	Right ☐		\$1,595
HR98	☐	Omit handrim on opposite side of the One Arm Drive (OAD)				NC
REAR WHEELS					Available	
RW01	☐	Mag ³			22" 24"	\$57
RW02	☐	Newton One - spoke wheel ⁴			22" 24"	NC
RW03	☐	Newton Gravity - ultralight wheel			22", 24", 25", 26"	\$335
RW04	☐	Spinergy Spox	Blk STD ☐	Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐	22", 24", 25", 26"	\$865
RW05	☐	Spinergy LX	Blk STD ☐	Pur ⁵ ☐ Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐ Pink ⁵ ☐ Grn ⁵ ☐ Org ⁵ ☐	22", 24", 25", 26"	\$1,095
RW07	☐	Spinergy CLX ⁶	Blk STD ☐	Pur ⁵ ☐ Wht ⁵ ☐ Blue ⁵ ☐ Red ⁵ ☐ Yel ⁵ ☐ Pink ⁵ ☐ Grn ⁵ ☐ Org ⁵ ☐	24", 25"	\$1,600
TIRES					Available	
AIRLESS						
TI01	☐	Soft Urethane 3.49cm (1 3/8") - Low Tread, black			22" 24"	NC
TI02	☐	Soft Urethane 3.49cm (1 3/8") - Medium Tread, black ⁷			22", 24", 25", 26"	\$105
TI04	☐	Soft Urethane 2.54cm (1") - No tread, black - <i>Shox</i>			22", 24", 25", 26"	\$125
TI08	☐	Pneumatic Airless insert 3.49cm (1 3/8") - Medium Tread ⁸			22", 24", 26"	\$90
PNEUMATIC						
TI05	☐	Pneumatic 3.49cm (1 3/8") Medium Tread			22", 24", 25", 26"	NC
TI06	☐	Pneumatic HP 2.54cm (1") - Low Tread, Puncture resistant, black - <i>SpeedLite</i>			22", 24", 25", 26"	\$110
TI07	☐	Pneumatic HP 2.54cm (1") - Medium Tread, Puncture resistant, black - <i>TrailBlazer</i>			24", 25", 26"	\$140
TI03	☐	Pneumatic 5.08cm (2") - Large Tread, black			22", 24", 25"	\$115

1- Offered with handrims on each side of the wheelchair; select the outer handrim in the handrims section; Only available with 24" wheel size; Not available with 21" and 22" wide; 2- Only standard handrim position available; 3- Not compatible with HP tires; Only available with aluminum or plastic coated handrim, standard position; 4- Not compatible with Shox tires; 5- color spokes require an additional 10 days lead-time; 6- Only available with 1" tires; 7- 22" is only available with Mags and Newton One rear wheels; 25" and 26" are not available with Newton Gravity wheels 8- Not available with Spinergy CLX, Spinergy LX 25", 26" and Spox 25", 26" rear wheels

Handrims						
HANDRIM		Available				
HR01	☐	Aluminum anodized		22", 24", 25", 26"		STD
HR61	☐	Aluminum black hard anodized ²		22", 24", 25"		\$75
HR02	☐	Plastic coated ¹		22", 24", 25", 26"		\$110
HR03	☐	High friction coated ^{1,2,3}		22", 24", 25", 26"		\$380
HR07-HR18 and HR65-HR71	☐	Newton Air Grip ² <i>See page 6 for the color selection and price</i>		22", 24", 25", 26"		
HR28	☐	Surge ^{1,2,3,4} (1 1/2" Oval handrim w/ Gripton high friction strip)		22", 24", 25", 26"		\$425
HR05	☐	Surge LT ^{1,2,3,4} (1 1/8" Oval handrim w/ Gripton high friction strip)		22", 24", 25", 26"		\$465
HR04	☐	Natural Fit ^{1,2,3,4}		22", 24", 25", 26"		\$335
HR62	☐	Simi H ^{1,2,3} (1 3/8" Oval handrim with high friction strip)		22", 24", 25", 26"		\$395
HR63	☐	Nova H ^{1,2,3} (1 1/4" Oval handrim with high friction strip)		22", 24", 25", 26"		\$425
HR64	☐	Optimum H ^{1,2,3} (1 1/8" heart-shaped handrim)		22", 24", 25", 26"		\$325
HR99	☐	Omit handrim				NC

1- Only standard and narrow handrim position. By default, the tab won't be cut with the narrow position; 2- Not available with Mag wheels; 3 - Not available with one arm drive; 4- 25" and 26" are not available in narrow position; 24" is not available with the Spinergy Spox, LX and CLX in narrow position; CLX rear wheel are not available with thumb piece

Handrims option						
ASSEMBLY POSITION						
HR29	☐	Standard Handrim position	Full tab			STD
HR030	☐	Narrow Handrim position no cut	Full tab			NC
HR30	☐	Narrow Handrim position with cut ⁵	Short tab 2 positions			\$32
HR31	☐	Super Narrow Handrim ⁵	Short tab 2 positions STD ☐ Short tab 1 position ☐			\$32
THUMB PIECE SELECTION FOR NATURAL FIT, SURGE, SURGE LT HANDRIMS						
HR23	☐	Standard grip				\$95
HR27	☐	Super grip				\$150
HR099	☐	Omit thumb piece				NC


5- Only available with Aluminum and Air Grip handrims;

AXLE ¹						
AX01	☐	Quick release axle				STD
AX03	☐	Quad release axle				\$135

1- Not required with one arm drive

REAR WHEEL CAMBER							
CM00	☐	0° camber					STD
CM03	☐	3° camber					NC
CM06	☐	6° camber					\$165

CENTER OF GRAVITY



X =

Choose position of rear wheel axle plate:

Measure distance X from front of back post to center of axle receiver.

Most stable												
2,5 1"	3,2 1/4"	3,8 1/2"	4,4 3/4"	5,1 2"	5,7 1/4"	6,3 1/2"	7 3/4"	7,6 3"	8,3 1/4"	8,9 1/2"	9,5 3/4"	10,2 4"
☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

If not indicated, default setting is at 3,8 cm/1.5"

Possible conflict between a seat depth under 40.6 cm (16") and a center of gravity over 6,3 cm (2.5").

Possible conflict between a 26" rear wheel and a center of gravity over 6,3 cm (2.5").

Motion Composites will select the closest possible center of gravity (COG) if an issue arises with the COG

WHEEL LOCK							
WL08	☐	Newton Wheel lock - push to lock				PRODUCT IMPROVED	STD
WL16	☐	Aluminum push to lock with extensions					\$83
WL02	☐	Pull to lock					NC
WL04	☐	Newton grade aid push to lock (<i>works best with pneumatic or high pressure tire</i>)					\$165
WL13 WL14	☐	6" removable extension handle ¹					\$83
WL05	☐	Scissors Lock					\$155
WL15	☐	Unilateral wheel lock - pull to lock ²	Left ☐	Right ☐			\$335
WL99	☐	Omit wheel locks					NC

1- Only available with Newton push to lock (WL08), pull to lock (WL02) and Newton Grade aid (WL04)

2- For more information about incompatibilities and restriction, refer to the table at page 7 and the "How-to documents" page of our website:

https://www.motioncomposites.com/en_ca/support-and-education/how-to-documents

Handrims							
HEIGHT ADJUSTABLE FLIP BACK ARMREST (<i>convertible to "T" armrest</i>) ¹							
AR01-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐	Unlocked STD ☐		\$380
AR01-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐	Unlocked STD ☐		\$380
AR02-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")	Locked ☐	Unlocked STD ☐		\$380
AR02-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")	Locked ☐	Unlocked STD ☐		\$380
HEIGHT ADJUSTABLE "T" ARMREST ¹							
AR13-610	☐	25.4cm (10") Desk length armpad ⁴	15.25 - 25cm (6" - 10")				\$350
AR03-812	☐	25.4cm (10") Desk length armpad	20.32 - 30.48cm (8" - 12")				\$350
AR03-1014	☐	25.4cm (10") Desk length armpad	25.40 - 35.56cm (10" - 14")				\$350
AR14-610	☐	35.56cm (14") Full length armpad ⁴	15.25 - 25cm (6" - 10")				\$350
AR04-812	☐	35.56cm (14") Full length armpad	20.32 - 30.48cm (8" - 12")				\$350
AR04-1014	☐	35.56cm (14") Full length armpad	25.40 - 35.56cm (10" - 14")				\$350
HEIGHT ADJUSTABLE SWING AWAY ARMREST ²							
AR05	☐	Tubular armrest - Short pad	20.32 - 27.94cm (8 - 11")				\$240
AR23	☐	Tubular armrest - Long pad	20.32 - 27.94cm (8 - 11")				\$240
AR06	☐	25.4cm (10") Desk Length flat armpad	20.32 - 27.94cm (8 - 11")				\$240
AR17	☐	35.56cm (14") Full Length flat armpad	20.32 - 27.94cm (8 - 11")				\$240
ARMREST OPTIONS							
AR12	☐	35.56cm (14") Full Length Armpad - Gel Ovation (<i>pair</i>) ³					\$165
AR99	☐	Omit armrest					NC

1- May have a 1/2" adjustment restriction on both limits of the range; 2- Could interfere with some rigid back rests; Not available with fixed carbon fiber side guards

3- Only available with full length armrest; Not available with swing away and desk length armrests; 4- May have some restriction with seat-to-floor height and rear wheel

SIDE GUARDS (<i>not available with Flip Back and "T" Armrest</i>)							
SG01	☐	Plastic side guards (<i>removable</i>)	Straight bracket - STD	Offset bracket ¹			\$210
SG02	☐	Carbon fiber side guards (<i>fixed</i>)					\$275
SG03	☐	Carbon fiber side guards (<i>removable</i>)	Straight bracket - STD	Offset bracket ¹			\$315
SG06	☐	Plastic fender side guards (<i>removable</i>)	Straight bracket - STD	Offset bracket ¹			\$295
SG04	☐	Carbon fiber fender side guards (<i>removable</i>)	Straight bracket - STD	Offset bracket ¹			\$550
SG99	☐	Omit side guard					NC

1- only compatible with 0° camber; increase width by 1/2" per side for a total of 1" ;

POSITIONING BELT				
SB01-S	☐	Velcro adjustable - Small 88.9cm (35") ¹		\$50
SB01-L	☐	Velcro adjustable - Long 152.40cm (60")		\$50
SB02-S	☐	Auto buckle - Small 88.9cm (35") ¹		\$95
SB02-M	☐	Auto buckle - Medium 121.92cm (48")		\$95
SB02-L	☐	Auto buckle - Long 152.40cm (60")		\$95
SB04-M	☐	BodyPoint Hip Belt - 2 point not padded - Medium 142.24cm (56")		\$95
SB04-L	☐	BodyPoint Hip Belt - 2 point not padded - Long 154.94cm (61")		\$95
SB05-S	☐	BodyPoint Hip Belt - 2 point padded - Small 129.54cm (51")		\$185
SB05-M	☐	BodyPoint Hip Belt - 2 point padded - Medium 142.24cm (56")		\$185
SB05-L	☐	BodyPoint Hip Belt - 2 point padded - Long 154.94cm (61")		\$185
SB06-S	☐	BodyPoint Hip Belt - 4 point padded - Small 129.54cm (51")		\$205
SB06-M	☐	BodyPoint Hip Belt - 4 point padded - Medium 142.24cm (56")		\$205
SB06-L	☐	BodyPoint Hip Belt - 4 point padded - Long 154.94cm (61")		\$205
SB03	☐	Hardware attachment for 2 extra points (1 pair)		\$17
SB08-M	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Medium 73.66 (18")		\$310
SB08-L	☐	BodyPoint EVOFLEX® Positioning Belt Rehab latch and Band Clamps - Long 93.98cm (24")		\$310
SB99	☐	Omit positioning belt		STD

1- Not recommended for seat width of 45.72cm (18") and more

HEADREST ¹				
AC01-S	☐	Profiled Headrest - Small 8.8x15.2cm (3.5"x6")		\$195
AC01-M	☐	Profiled Headrest - Medium 11.4x17.8cm (4.5"x7")		\$195
AC01-L	☐	Profiled Headrest - Large 14x2.3cm(5.5"x8")		\$195
AC28	☐	Headrest mounting hardware with tension bar		\$320

1- Only available with push handles

ACCESSORIES				
AC03	☐	Anti-tippers		\$150
AC29	☐	Swing-away anti-tipper ¹ Left ☐ Right ☐		\$165
AC27	☐	Tip assist ²		\$67
AC06	☐	Cane and crutch holder Left ☐ Right ☐		\$130
AC08	☐	Spoke guards ³ Available: 22", 24", 26"		\$125
AC10	☐	Seat pouch		\$83
AC30	☐	Newton multi-purpose pouch		\$62
AC26	☐	BodyPoint Mobility Bag		\$135
AC23	☐	Newton Backpack		\$130
AC12	☐	Velcro Closing Strap		\$57
AC13	☐	Tool kit		\$50
AC16	☐	Motion Composites Polo Shirt W/S ☐ W/M ☐ W/L ☐ M/S ☐ M/M ☐ M/L ☐ M/XL ☐ M/XXL ☐ M/XXXL ☐		\$36

1- Must select the pair (left and right) with HD option; Only available with rear seat to floor height between 34,3cm (13 1/2") and 50,2cm (19 3/4"); 2- Cannot be combined with Anti Tippers

3- Not available with Mag wheels and Spineray

Colors																				
Options ¹	Black	High Gloss Carbon Fiber	Sunkissed Orange	Burgundy	Sapphire Blue	Monster Green	Charcoal	Fuchsia	Steel Blue	Ferrari Red	Acid Green	Electric Purple	Caribbean Blue	White	Pink Pearl	Plum Purple	Sky Blue	Black Cherry	Khaki Green (matte)	Desert Sand (matte)
																				
AirGrip	☐ \$110	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Frame	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
																				
Highlight ²	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
FC99	☐	Custom Color Specify PPG Paintit color:	additional 10 days lead-time																	\$390

1- Color representation may vary from one monitor to another. Therefore, the actual paint color on your wheelchair might differ slightly from what you see on your screen.; Finish between Airgrip and frame might be different;

2- To see different highlight, visit our website: https://www.motioncomposites.com/en_intl/products/folding-wheelchairs/veloce

Frame length chart

Frame length	Seat Depth						
	35.56 (14")	38.10 (15")	40.64 (16")	43.18 (17")	45.72 (18")	48.26 (19")	50.80 (20")
STD	N/A						
1							N/A
2						N/A	N/A
-1	N/A	N/A					
-2	N/A	N/A	N/A				

Unilateral wheel lock restrictions

Seat depth: shall be 16 in and greater		
Rear wheel: shall be 24 in and less		
"T" or flip-back armrest only compatible with 0° Camber		
One arm drive: Not compatible with "T" or flip-back armrest		
"T" or flip-back armrest may require to move the rear wheels outwards		
Not compatible with wheel lock lever extension		
Rear wheel diameter	Seat depth (in)	COG Compatibility Range (in)
20 in	16+	1.75 to 4
22 in	16+	2.5 to 4
24 in	16+	1 to 4



CUSTOMIZATION STARTS HERE!

With EVO Custom, whether it's a subtle tweak for comfort or mobility, or a fully reimagined component tailored to your unique needs, we're here to support you.



Explore the
EVO Custom Catalog.

You can include your request or reference an existing customization from our catalog in the notes section below.



Have a customization in mind or a specific request? The **EVO Custom Request Form** is the best place to start.

Notes :